

Temway Chassis Specials | Order Form



Ordering Branch / Agent:	Branch contact:
Branch Sales Order No.	
Branch transfer Order No.	
CUSTOMER DETAILS:	
Customer:	Customer order number:
	Contact name:
Deliver to:	Project:
	Request delivery date:

Double/ single sided tee off quantities	L RED	L2 WHITE	L3 BLUE	N BLACK
12/6				
18/6				
24/12				
30/15				
36/18				
42/21				
48/24				
60/30				
72/36				

Application

DC chassis (2 pole)

1 Phase and neutral

2 Phase

1 Phase and neutral

3 Phase

4 Pole (3P + N: XB only)

Cross location of tee-offs at left

Type and entry

XA Top feed

XB Bottom feed

XBSSL (Left side)

XBSSR (Right side)

PXB

XC

Dual feed (standard)

No feed

(show location on the drawing)

MCCB

E-S125/ZS125 3Pole=90mm

E-S160-250/ZS250 3Pole=105mm

S250PE 3Pole=105mm

E-S400 3Pole=140mm

E-S125/ZS125 4Pole=120mm

E-S160-250/ZS250 4Pole=140mm

Busbar rating and notes

630 Amp

800 Amp

1000 Amp (XC only)

Description _____

Due date _____

NHP Ref. No. _____

Quantity _____

Supplier reference No. _____

Works order No. _____

Delivery

Customer Workshop

Please send this request form to NHP Electrical Engineering Products (Australia) Pty Ltd
ast@nhp.com.au or by fax on 1300 NHP FAX