

MOD6⁺



NHP CERTIFIED
C CURVE 6.00kA
AS/NZS TESTED

NHP



MOD6⁺ Panelboard Solutions

- AS/NZS 61439-3
- Neutral Ral 7035 colour
- IP40 MOD6+ One
- IP56 MOD6+ Prime
- Suits MOD6+ circuit protection

NHP MOD6+ Panelboards



Series	MOD6+ One	MOD6+ Prime
		
IP Rating	IP40	IP56
Width	530mm	600mm
Depth (including door, excluding door handle)	153mm	200mm
Colour	Light Grey RAL 7035	Light Grey RAL 7035
Material mild steel	1.0mm	1.6mm
MCB/RCBO Type	MOD6+	MOD6+
Chassis rating	250A	250A
Chassis type	Encapsulated	Encapsulated
Spare horizontal DIN spaces	16	18
MCB pole capacity	24, 36, 48, 60 & 84	24, 36, 48, 60 & 84
Isolator main switch	160A, 250A	250A
MCCB main switch option	100A, 160A, 200A	100A, 160A, 200A
Door hinged (semi concealed)	RH Standard	RH Standard
Escutcheon (white)	Lift-off only	Hinged
Door handle - semi flush	Standard	Standard
E/N bar rating	250A	250A
3 Point locking	-	Standard
Door lock CL001	Standard	Standard
Door lock option 92268, 42886, PWD-E, K144	Option	Option
Door lock option non lockable or Pad lockable	Option	Option
Rainhood	-	Option
Plinth	-	Option
Flush mounting kit	Option	-
Gland plate aluminium	-	Option
Accessory module - horizontal DIN rail cut-out	21, 42-way 432mm 63- way 648mm	48-way 432mm
Accessory module - blank escutcheon	2M- 432mm 3M- 648mm	2M- 432mm



Scan this QR code
for additional
information