

800TCXAV

Allen-Bradley 800T Contact Block FS Terminal Guard Pentuff
Pentri. 1 N.O. 1 N.C. for 30.5mm PB



Allen-Bradley

by ROCKWELL AUTOMATION

PUSHBUTTON AND PILOT LIGHTS



Component type	Auxiliary contact block
Range	800T/H Pushbutton
Model	N/A
Product status	Existing

The Allen-Bradley 800T/H range of 30.5mm mount operators are designed and constructed to perform in the most demanding industrial environments. The range includes pushbuttons, selector switches, emergency stops, pilot lights. Available in both metal and plastic types with a modular design allowing for easy selection, configuration and assembly of components to form the operator control device.

ELECTRICAL

Number of contacts as normally open contact	1.0
Number of contacts as normally closed contact	1.0
Rated insulation voltage U_i	300.0 V
Rated operation current I_e at AC-15, 120 V	3.0 A
Rated operation current I_e at AC-15, 240 V	0.75 A
Rated operation current I_e at DC-13, 24 V	1.0 A
Rated operation current I_e at DC-13, 110 V	0.25 A
Rated operation current I_e at DC-13, 125 V	0.22 A
Contact rating current (Min)	1.0 mA
Contact rating voltage (Min)	5.0 V