

# 800TXAY

Allen-Bradley 800T Contact Block Stackable Sealed Switch 1  
N.C. 1 N.O. Contact for 30.5mm Pushbutton



**Allen-Bradley**

by ROCKWELL AUTOMATION

PUSHBUTTON AND PILOT LIGHTS



<b>Component type</b>	Auxiliary contact block
<b>Range</b>	800T/H Pushbutton
<b>Model</b>	N/A
<b>Product status</b>	Existing

The Allen-Bradley 800T/H range of 30.5mm mount operators are designed and constructed to perform in the most demanding industrial environments. The range includes pushbuttons, selector switches, emergency stops, pilot lights. Available in both metal and plastic types with a modular design allowing for easy selection, configuration and assembly of components to form the operator control device.

## ELECTRICAL

Number of contacts as normally open contact	1.0
Number of contacts as normally closed contact	1.0
Rated insulation voltage $U_i$	300.0 V
Rated operation current $I_e$ at AC-15, 120 V	3.0 A
Rated operation current $I_e$ at AC-15, 240 V	1.5 A
Rated operation current $I_e$ at DC-13, 24 V	2.5 A
Rated operation current $I_e$ at DC-13, 125 V	0.55 A
Contact rating current (Min)	10.0 mA
Contact rating voltage (Min)	5.0 V