

CA89M31110VAC

S+S CA8 Contactor Mini 4kW 4Pole 110VAC Coil 3NO 1NC
Contact Auxiliary



CONTACTORS



Component type	Power contactor, AC switching
Range	CA8 Mini
Model	N/A
Product status	Existing

The Sprecher + Schuh CA8 miniature contactors and starters are a compact and reliable method of controlling motors of 5.5kW or less. Ideal for applications where space is limited. Components are DIN-rail mountable and clearly marked and dispatched in the open position ready for assembly. Fittings are also included on the base mounting for quick installation and modification.

ELECTRICAL

Number of normally open contacts as main contact	3
Number of normally closed contacts as main contact	1
Rated operation current Ie at AC-3, 400 V	8.5 A
Rated operation power at AC-3, 400 V	4 kW
Rated operation current Ie at AC-1, 400 V	20 A
Max. rated operation voltage Ue AC	690 V
Voltage type for actuating	AC
Control supply voltage Us at AC 50HZ	110 V
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as normally closed contact	0
Rated operation current Ie at AC-3, 690 V	4.9 A
Rated operation power at AC-3, 690 V	4 kW
Rated operation power at AC-4, 400 V	1.1 kW
Control supply voltage Us at AC 60HZ	120 V
Power consumption, AC coil pickup	35 VA
Power consumption, AC coil hold-in	5 VA
Type of electrical connection of main circuit	Screw connection
Rated operation current Ie at AC-4, 400 V	3.6 A

CONSTRUCTION

IP rating	IP20
Mounting method	Screw mounting

DIMENSIONS

Height	56 mm
Width	44.9 mm
Depth	53 mm
Weight	0.16 kg

CA89M31110VAC

S+S CA8 Contactor Mini 4kW 4Pole 110VAC Coil 3NO 1NC
Contact Auxiliary




CONTACTORS

sprecher+schuh

DIMENSIONAL DIAGRAM

Dimensions are in millimeters (inches). Dimensions not intended for manufacturing purposes.



REVERSING CONTACTORS & ACCESSORIES

Contactor with...		Dim. [mm]
reversing with mechanical interlock		89.8
with aux. contact block		78.7
with timer	on contactor	81.7
	at side of contactor	66.9
with protection element		
with nameplate		51