# CA8P31

**S+S CA8 Auxiliary Contact with 3NO  Contacts and 1NC Contact**

CONTACTORS




| | |
|---|---|
| **Component type** | Auxiliary contact block |
| **Range** | CA8 Mini |
| **Model** | N/A |
| **Product status** | Existing |

The Sprecher + Schuh CA8 miniature contactors and starters are a compact and reliable method of controlling motors of 5.5kW or less. Ideal for applications where space is limited. Components are DIN-rail mountable and clearly marked and dispatched in the open position ready for assembly. Fittings are also included on the base mounting for quick installation and modification.

| | | |
|---|---|---|
| **ELECTRICAL** | **Number of contacts as normally open contact** | 3 |
| | **Number of contacts as normally closed contact** | 1 |
| | **Rated insulation voltage Ui** | 690 V |
| | **Rated operation current Ie at AC-15, 24 V** | 3 A |
| | **Rated operation current Ie at AC-15, 120 V** | 3 A |
| | **Rated operation current Ie at AC-15, 240 V** | 2 A |
| | **Rated operation current Ie at AC-15, 400 V** | 1.2 A |
| | **Rated operation current Ie at DC-13, 24 V** | 2.3 A |
| | **Rated operation current Ie at DC-13, 110 V** | 0.55 A |
| | **Rated operation current Ie at DC-13, 220 V** | 0.27 A |
| | **Min. contact rating current** | 2 mA |
| | **Min. contact rating voltage** | 15 V |
| | **Rated operation current Ie at AC-15, 230 V** | 2 A |
| **CONSTRUCTION** | **Mounting method** | Top mounting |



Published on 31 May 2026