

# D7BX10

Sprecher and Schuh D7 Contact Block Base Mount 1 NO for 22.5mm Pushbutton Operators



PUSHBUTTON AND PILOT LIGHTS

**sprecher+**  
**schuh**



<b>Component type</b>	Auxiliary contact block
<b>Range</b>	D7
<b>Model</b>	N/A
<b>Product status</b>	Existing

The Sprecher + Schuh D7 line of operator control devices is a diverse range of 22.5mm mount pushbuttons, pilot lights, selector switches, and emergency stops, ideal for use in applications requiring reliable performance. Modular design allows for easy configuration and assembly. Available in plastic and metal types, optional accessories include enclosures, legend plates, padlocks, and colour caps.

## ELECTRICAL

Number of contacts as normally open contact	1
Rated insulation voltage $U_i$	690 V
Rated operation current $I_e$ at AC-15, 120 V	6 A
Rated operation current $I_e$ at AC-15, 240 V	3 A
Rated operation current $I_e$ at AC-15, 400 V	1.8 A
Rated operation current $I_e$ at DC-13, 125 V	0.55 A
Rated operation current $I_e$ at DC-13, 250 V	0.27 A
Min. contact rating current	5 mA
Min. contact rating voltage	17 V

## CONSTRUCTION

Mounting method	Base mounting
-----------------	---------------