D7ME2

Sprecher and Schuh D7 Pushbutton 22.5 mm Head Only Metal MOM Extended Black Cap Non Illuminated





Component type	Front element for push button
Range	D7
Model	N/A
Product status	Existing

The Sprecher+Schuh D7 line of operator control devices are a diverse range of 22.5mm mount pushbuttons, pilot lights, selector switches, emergency stops, ideal for use in applications requiring reliable performance. A modular design allows for easy configuration and assembly. Available in plastic and metal types, optional accessories include enclosures, legend plates, padlocks and colour caps.

Colour button Black Type of button High Labelled No Material front ring Metal Colour front ring Chrome Degree of protection (IP), front side IP66 Construction type lens Round With protective cover No With front ring Yes Degree of protection (NEMA), front side 5 Switching function latching No Spring-return No			
CONSTRUCTION Labelled No	CONSTRUCTION	Colour button	Black
CONSTRUCTION Material front ring Colour front ring Colour front ring Degree of protection (IP), front side Construction type lens Round With protective cover No With front ring Yes Degree of protection (NEMA), front side Switching function latching No		Type of button	High
Colour front ring Chrome Degree of protection (IP), front side IP66 Construction type lens Round With protective cover No With front ring Yes Degree of protection (NEMA), front side 5 Switching function latching No		Labelled	No
Degree of protection (IP), front side IP66 Construction type lens Round With protective cover No With front ring Yes Degree of protection (NEMA), front side 5 Switching function latching No		Material front ring	Metal
Degree of protection (IP), front side IP66 Construction type lens Round With protective cover No With front ring Yes Degree of protection (NEMA), front side 5 Switching function latching No		Colour front ring	Chrome
With protective cover No With front ring Yes Degree of protection (NEMA), front side 5 Switching function latching No		Degree of protection (IP), front side	IP66
With front ring Yes Degree of protection (NEMA), front side 5 Switching function latching No		Construction type lens	Round
Degree of protection (NEMA), front side 5 Switching function latching No		With protective cover	No
Switching function latching No		With front ring	Yes
		Degree of protection (NEMA), front side	5
Spring-return No	MECHANICAL	Switching function latching	No
		Spring-return	No
Vibration acceleration (Max) 10.0 m/s ²		Vibration acceleration (Max)	10.0 m/s ²
Vibration frequency, operational (Max) 2000.0 Hz		Vibration frequency, operational (Max)	2000.0 Hz
Shock acceleration (Max) 100.0 g		Shock acceleration (Max)	100.0 g
Number of command positions 1.0		Number of command positions	1.0
PHOTOMETRIC Suitable for illumination No	PHOTOMETRIC	Suitable for illumination	No
Hole diameter 22.5 mm	DIMENSIONS	Hole diameter	22.5 mm
DIMENSIONS Width opening 29.6 mm		Width opening	29.6 mm
Height opening 14.0 mm		Height opening	14.0 mm