

# D7MKM3303R

Sprecher and Schuh D7 Key Selector Switch 22.5 mm 3 Position  
Metal Maint Key Rtn All Code 3803



**sprecher+schuh**  
PUSHBUTTON AND PILOT LIGHTS

|                |                                   |
|----------------|-----------------------------------|
| Component type | Front element for selector switch |
| Range          | D7                                |
| Model          | N/A                               |
| Product status | Existing                          |



The Sprecher+Schuh D7 line of operator control devices are a diverse range of 22.5mm mount pushbuttons, pilot lights, selector switches, emergency stops, ideal for use in applications requiring reliable performance. A modular design allows for easy configuration and assembly. Available in plastic and metal types, optional accessories include enclosures, legend plates, padlocks and colour caps.

|              |  |                       |
|--------------|--|-----------------------|
| ELECTRICAL   | Type of control element                | Key                   |
|              | Colour control element                 | Black                 |
|              | Colour indicator light cap             | White                 |
|              | Material front ring                    | Metal                 |
| CONSTRUCTION | Colour front ring                      | Other                 |
|              | Degree of protection (IP), front side  | IP66                  |
|              | With front ring                        | Yes                   |
|              | Degree of protection (NEMA)            | Other                 |
| MECHANICAL   | Number of switch positions             | 3.0                   |
|              | Switching function latching            | No                    |
|              | Spring-return                          | No                    |
|              | Vibration acceleration (Max)           | 10.0 m/s <sup>2</sup> |
|              | Vibration frequency, operational (Max) | 2000.0 Hz             |
|              | Shock acceleration (Max)               | 100.0 g               |
|              | Mechanical life (service cycles)       | 300000.0 cycles       |
| PHOTOMETRIC  | Suitable for illumination              | No                    |
|              | Hole diameter                          | 22.5 mm               |
| DIMENSIONS   | Width opening                          | 29.6 mm               |
|              | Height opening                         | 47.1 mm               |
| ENVIRONMENT  | Operating temperature                  | -25 - 70 °C           |

# D7MKM3303R

Sprecher and Schuh D7 Key Selector Switch 22.5 mm 3 Position  
Metal Maint Key Rtn All Code 3803



**sprecher+schuh**  
PUSHBUTTON AND PILOT LIGHTS

## DIMENSIONAL DIAGRAM

