

# D7PMM64

Sprecher and Schuh D7 PushButton 22.5mm Momentary  
Mushroom Plastic Head 60 mm Red



|                       |  |
|-----------------------|--|
| <b>Component type</b> | Front element for mushroom push-button |
| <b>Range</b>          | D7                                     |
| <b>Model</b>          | N/A                                    |
| <b>Product status</b> | Existing                               |

The Sprecher+Schuh D7 line of operator control devices are a diverse range of 22.5mm mount pushbuttons, pilot lights, selector switches, emergency stops, ideal for use in applications requiring reliable performance. A modular design allows for easy configuration and assembly. Available in plastic and metal types, optional accessories include enclosures, legend plates, padlocks and colour caps.

|                     |  |                       |
|---------------------|--|-----------------------|
| <b>ELECTRICAL</b>   | Electrical life at Un, In (service cycles) | 500000.0 cycles       |
| <b>CONSTRUCTION</b> | Suitable for emergency stop                | Yes                   |
|                     | Colour button                              | Red                   |
|                     | Material front ring                        | Plastic               |
|                     | Colour front ring                          | Other                 |
|                     | Degree of protection (IP)                  | IP65/IP66/IP69K       |
|                     | Degree of protection (NEMA)                | Other                 |
| <b>MECHANICAL</b>   | Switching function latching                | No                    |
|                     | Spring-return                              | No                    |
|                     | Unlocking method                           | Pull-release          |
|                     | Mechanical life (service cycles)           | 1.0E7 cycles          |
|                     | Vibration acceleration (Max)               | 10.0 m/s <sup>2</sup> |
|                     | Vibration frequency, operational (Max)     | 2000.0 Hz             |
| <b>PHOTOMETRIC</b>  | Shock acceleration (Max)                   | 100.0 g               |
|                     | Suitable for illumination                  | No                    |
| <b>DIMENSIONS</b>   | Diameter cap                               | 60.0 mm               |
|                     | Hole diameter                              | 22.5 mm               |
|                     | <b>ENVIRONMENT</b>                         | Operating temperature |