

## D7X01S

Sprecher and Schuh D7 Contact Block 1 NC for 22.5 mm  
Pushbutton Operators Self Monitoring



Component type	Auxiliary contact block
Range	D7
Model	N/A
Product status	Existing

The Sprecher+Schuh D7 line of operator control devices are a diverse range of 22.5mm mount pushbuttons, pilot lights, selector switches, emergency stops, ideal for use in applications requiring reliable performance. A modular design allows for easy configuration and assembly. Available in plastic and metal types, optional accessories include enclosures, legend plates, padlocks and colour caps.



### ELECTRICAL

Number of contacts as normally closed contact	1.0
Rated insulation voltage $U_i$	690.0 V
Rated operation current $I_e$ at AC-15, 120 V	6.0 A
Rated operation current $I_e$ at AC-15, 240 V	3.0 A
Rated operation current $I_e$ at AC-15, 400 V	1.8 A
Rated operation current $I_e$ at DC-13, 125 V	0.55 A
Rated operation current $I_e$ at DC-13, 250 V	0.27 A
Contact rating current (Min)	5.0 mA
Contact rating voltage (Min)	17.0 V

# D7X01S

Sprecher and Schuh D7 Contact Block 1 NC for 22.5 mm  
Pushbutton Operators Self Monitoring



**sprecher+schuh**  
PUSHBUTTON AND PILOT LIGHTS

## DIMENSIONAL DIAGRAM

