

KL3062A

Klaxon Flashguard Beacon LED Steady or Flashing Mode IP65
11-35V DC Ceiling or Wall Mnt Ambers



Component type	Signalling device
Range	Flashguard
Model	N/A
Product status	Existing

The Klaxon Flashguard Beacons provide highly visible and reliable signalling solutions in industrial and commercial environments. Easy to install, LED or Xenon options available, fitted with a diffuser providing greater visibility and spread of light. The standard option includes a terminal block, 27mm deep base, seal, grommet and a compact appearance.



ELECTRICAL	Rated operation current I _e	0.05 A
	Nominal voltage	11 - 35 V
	Type of current	DC
	Electricity consumption	0.05 A
COMMUNICATION	Compatible with Apple HomeKit	No
	Compatible with Google Assistant	No
	Compatible with Amazon Alexa	No
CONSTRUCTION	Type of indication	Optic
	Colour of lamp hood	Orange
	Mounting method	Surface mounting
	Material housing	Polycarbonate (PC)
	Colour housing	White
	Degree of protection (IP)	IP65
MECHANICAL	Suitable for wall mounting	Yes
	Suitable for ceiling mounting	Yes
PHOTOMETRIC	Lamp type	LED
	Type of optical signal	Flash light
DIMENSIONS	Weight	0.14 kg
ENVIRONMENT	Ambient temperature during operating	-20 - 70 °C
CERTIFICATES/APPROVALS	For Ex-zone gas	None
	For Ex-Zone dust	None

KL3062A

Klaxon Flashguard Beacon LED Steady or Flashing Mode IP65
11-35V DC Ceiling or Wall Mnt Ambers



DIMENSIONAL DIAGRAM

Standard and Fire Style

