## LE2201784

Sprecher and Schuh L2 Cam Switch Switch Body 4 Pole Off On 20A Panel Mount





Component type	Off-load switch
Range	L2 Cam Switch
Model	N/A
Product status	Existing

The Sprecher+Schuh L2 range of rotary cam switches are designed for use in control and load switching based applications rated up to 25A. Available in a wide range of faceplate designs, frame sizes, switch body designs and accessories to suit various switching configurations. The modular construction allows for quick and easy assembly and installation while providing reliable operation.

	Newsbarr of males	4.0
ELECTRICAL	Number of poles	4.0
	Rated operation power at AC-3, 400 V	9.0 kW
	Rated operation current le at AC-15, 230 V	7.0 A
	Rated operation current le at AC-15, 400 V	5.0 A
	Rated operation current le at AC-22a, 690V	20.0 A
	Rated operation current le at AC-22a, 220-500V	20.0 A
	Rated operation current le at AC-21a, 690V	20.0 A
	Rated operation current le at AC-1, 690V	20.0 A
	Ithe, thermal current (enclosed)	20.0 A
	Ith, thermal current (open)	25.0 A
	Number of auxiliary contacts as normally closed contact	0.0
	Number of auxiliary contacts as normally open contact	0.0
	Number of auxiliary contacts as change-over contact	0.0
	Type of electrical connection of main circuit	Screw connection
CONSTRUCTION	Model	On/Off switch
	Mounting method	Front mounting
	Material housing	Plastic
	Wire/conductor size, rigid cable	1.5 - 6 mm <sup>2</sup>
	Wire/conductor size, flex cable	1.5 - 4 mm²
	Degree of protection (IP), front side	IP20
	Suitable for front mounting	Yes
	Complete device in housing	No
MECHANICAL	With zero (off) position	Yes
	Mechanical life (service cycles)	1000000.0 cycles

## LE2201784

Sprecher and Schuh L2 Cam Switch Switch Body 4 Pole Off On 20A Panel Mount



MECHANICAL	Number of switch positions	2.0
	With retraction in 0-position	No
DIMENSIONS	Depth	57.0 mm
	Width	55.0 mm
	Height	55.0 mm
ENVIRONMENT	Operating temperature	-25 - 60 °C



## **DIMENSIONAL DIAGRAM**



