

2232434012VACDC

Finder 22 Series Modular Contactor 25A 12V AC DC Coil 2
Normally Open Contacts



GENERAL PURPOSE RELAYS



Component type	Installation contactor for distribution board
Range	Modular Contactor
Model	N/A
Product status	Existing

The Finder range of modular contactors are reliable, efficient switching devices for controlling electrical loads in various industrial and commercial applications. Available in 17.5mm, 36mm and 53.5mm width with AC and DC variants as well as 2 and 4 contact versions and a switching range from 25A to 63A.

ELECTRICAL

Rated operation current	25 A
Rated operating voltage	250-400 V
Voltage type for actuating	AC/DC
Rated excitation voltage 2	9.6-13.2 V
Rated excitation voltage	9.6-13.2 V
Rated operation current I _e at AC-1	25 A
Rated operation current I _e at AC-3	10 A
Number of contacts as normally open contact	2
Number of contacts as normally closed contact	0
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC/DC

CONSTRUCTION

Hum-free	Yes
IP rating	IP20
Additional equipment possible	Yes
With day/night function	No

PHOTOMETRIC

Max. incandescent lamp load	2000 W
Max. load fluorescent lamp	500 VA

DIMENSIONS

Height	88.8 mm
Width	17.5 mm
Depth	60.8 mm
Width in number of modular spacings	1

2232434012VACDC

Finder 22 Series Modular Contactor 25A 12V AC DC Coil 2
Normally Open Contacts



GENERAL PURPOSE RELAYS



DIMENSIONAL DIAGRAM

Type 22.32
Screw terminal

