48290574

Socomec TF-80 Rogowski Coil CT 150-600A 80mm Diameter for Digiware and DIRIS A-xx





Component type	Current transformer		
Range	TF Rogowski Coil		
Model	N/A		
Product status	New Item		

The Socomec Rogowski Coil CTs are designed for use with Diris A-40, A-200, and Digiware I modules. They are quick to install, have a wide range of nominal current, and are highly accurate. Best suited for larger currents going up to 6000A nominal current. Each CT is sold with a wide range of accessories to allow for flexibility in installation position within a switchboard or distribution board.

	Primary rated current	600 A	
ELECTRICAL	Secondary current on CT	0.1 A	
	Rated operating frequency	50-60 Hz	
	Max. operating voltage (Umax)	600 V	
	Accuracy class	0.2S	
	Over current limiting factor	FS 10	
	Secondary rated apparent power	0.1 VA	
CONSTRUCTION	Calibrated	Yes	
	Current transformer type	Split core	
	Material housing	Plastic	
	Model	Attachable current transformer	
	With shock protection	Yes	
	Snap mounting	Yes	
	With copper rail	Yes	
	Secondary connection	Plug-in connection	
DIMENSIONS	Number of primary inputs	1	
	Opening diameter	80 mm	
	Height opening	80-80 mm	
	Width opening	80-80 mm	
ENVIRONMENT	Storage temperature	-2585 °C	

48290574


Socomec TF-80 Rogowski Coil CT 150-600A 80mm Diameter for Digiware and DIRIS A-xx



DIMENSIONAL DIAGRAM


Dimensions in/mm

	TF-40	TF-80	TF-120	TF-200	TF-300	TF-600	
D (Ø)	1.57	3.15	4.72	7.87	11.81	23.62	
	40	80	120	200	300	600	
L	4.96	9.88	14.84	24.72	37.09	74.21	
	126	251	377	628	942	1885	
Integrator	5.04 x 0.75 x 0.6 128 x 19 x 15						





ELECTRICAL CONNECTION DIAGRAM



48290574

Socomec TF-80 Rogowski Coil CT 150-600A 80mm Diameter for Digiware and DIRIS A-xx



RELATED PRODUCTS

ACCESSORY



Item No: 48290600 Required: No

Description: Socomec Sealable Cover for TE/

TR/iTRs/TF CTs



Item No: 48290670 Required: No

Description: Socomec RJ12 x 3 Female to Female Connectors Extension for TF CTs