800TCFX6D4

Allen-Bradley 800T PB 30.5mm FS Terminal Grd Mush. Hd 2 Pos. Push Pull 1N.C. Late Break Contact Red





Component type	Push button, complete
Range	800T/H Pushbutton
Model	N/A
Product status	Existing

The Allen-Bradley 800T/H range of 30.5mm mount operators are designed and constructed to perform in the most demanding industrial environments. The range includes pushbuttons, selector switches, emergency stops, pilot lights. Available in both metal and plastic types with a modular design allowing for easy selection, configuration and assembly of components to form the operator control device.

ELECTRICAL	Number of contacts as normally open contact	0.0	
	Number of contacts as normally closed contact	1.0	
	Type of electric connection	Screw connection	
CONSTRUCTION	Colour button	Red	
	Type of button	Mushroom	
	With front ring	Yes	
	Material front ring	Metal	
	Degree of protection (IP)	IP65/IP66	
MECHANICAL	Number of command positions	2.0	
	Switching function latching	No	
	Shock acceleration (Max)	100.0 g	
	Vibration acceleration (Max)	10.0 m/s²	
	Vibration frequency, operational (Max)	2000.0 Hz	
PHOTOMETRIC	Suitable for illumination	No	
DIMENSIONS	Hole diameter	30.5 mm	
	Operator diameter	41.3 mm	

800TCFX6D4

Allen-Bradley 800T PB 30.5mm FS Terminal Grd Mush. Hd 2 Pos. Push Pull 1N.C. Late Break Contact Red



DIMENSIONAL DIAGRAM

Non-Illuminated Push-Pull Buttons						
Cat. No.		Transformer Type				
Suffix	Description	Dim.		Ship. Wt.		
D4	One Shallow Contact Block	А	2-1/32 (51.6)	5 oz. (0.14 kg)		