CSB08SW

NHP MOD6 CSB Insulated Loadcentre 8 Way DIN Surface Door White

MOD6
LOADCENTRES AND POLE COVERS



Component type	Small distribution board
Range	CSB
Model	N/A
Product status	Discontinued

NHP's CSB surface-mounted insulated loadcentres offer a compact, cost effective method of mounting DIN circuit protective devices in domestic or commercial settings. The CSB loadcentres can accommodate a wide range of current ratings, making them suitable for various applications. The CSB surface or flush-mount options range from 8 up to 36 way with either transparent or white door.

ELECTRICAL	**Rated current In**	100 A
	Number of outgoing ways	8
	Number of poles, 18mm pitch	8
	Max. rated operation voltage Ue AC	415 V
	Rated insulation voltage Ui	500 V
	Neutral terminal block	Yes
	Neutral bar rated current	100 A
	Earthing terminal block	Yes
CONSTRUCTION	**Spare DIN equipment space (poles)**	8
	DIN-rail	Yes
	Number of rows	1
	Material housing	Plastic
	Colour	White
	IP rating	IP40
	Type of cover	Door
	Transparent cover/door	No
	With lock	No
	Mounting method	Surface mounted (plaster)
DIMENSIONS	**Width in number of modular spacings**	8
	Height	200 mm
	Width	185 mm
	Depth	94 mm

Published on 02 September 2026