ILC4SLDCB803P

NHP DIN-T Meter Isolator Pole Cover 4 Way Surface and 3Pole 80A 10kA MCB C Curve LOCKDIN

DIN-T™
LOADCENTRES AND POLE COVERS



Component type	Small distribution board
Range	Meter Isolator
Model	N/A
Product status	Discontinued

NHP meter isolator kits provide a safe and efficient way to disconnect, isolate and lockout electrical meters in residential or commercial applications.

ELECTRICAL	Rated current In	100 A
	Number of outgoing ways	3
	Number of poles, 18mm pitch	3
	Number of poles, 27mm pitch	3
	Max. rated operation voltage Ue AC	415 V
	Rated insulation voltage Ui	500 V
	Number of poles main switch	3
	Main switch rated current	80 A
	Circuit breaker as main switch	Yes
	Neutral terminal block	No
	Earthing terminal block	No
CONSTRUCTION	DIN-rail	Yes
	Number of rows	1
	Material housing	Plastic
	Colour	Grey
	RAL-number	7035
	IP rating	IP40
	Type of cover	Door
	Transparent cover/door	Yes
	With lock	No
	Mounting method	Surface mounted (plaster)
DIMENSIONS	Width in number of modular spacings	4
	Height	175 mm
	Width	90 mm
	Depth	100 mm

Published on 08 December 2025

ILC4SLDCB803P

NHP DIN-T Meter Isolator Pole Cover 4 Way Surface and 3Pole 80A 10kA MCB C Curve LOCKDIN

DIN-T™
LOADCENTRES AND POLE COVERS

RELATED PRODUCTS

ACCESSORY



Item No: ILCSB

Required: No

Description: NHP DIN-T ILC Insulated Pole Cover Lead Sealing Bracket to suit ILC

Published on 08 December 2025