

EASSM2310S

Carlo Gavazzi Timer Relays Timer On Delay 24 to 230V AC DC
Supply SCR Output 0.5 to 10 Seconds



Component type	Timer relay
Range	Timer Relays
Model	N/A
Product status	Existing

The Carlo Gavazzi Timers are ideal in a wide range of applications in automation, such as motor control centres, packaging machinery, HVAC equipment, control panels and process control systems. The range offers solutions for various functions, mountings, and output type.

ELECTRICAL

Voltage type for actuating	AC
Rated control supply voltage Us at AC 60HZ	264-21.6 V
Rated control supply voltage Us at AC 50HZ	346-440 V
Number of outputs, delayed, change-over contact	1
Type of electric connection	Screw connection
Function delay-on energization	Yes
Function delay on de-energization	No
Function floating contact on energization	No
Function floating contact on de-energization	No
Function star-delta	No
Function pulse shaping	No
Function flashing, starting with pause, fixed time	No
Function flashing, starting with pulse, fixed time	No
Clock function, starting with pause, variable	Yes
Clock function, starting with pulse, variable	Yes
Time range	0.5-10 s
Time setting accuracy	5 %
Power supply reset time	50 ms
Power consumption	0.5 VA
Electrical lifespan (control contacts)	200000 c (contacts)

MECHANICAL

Suitable for DIN rail (top hat rail) mounting	Yes
Mechanical lifetime (control contacts)	3.0E7 c (contacts)
Max. shock acceleration	50 g
Max. vibration acceleration	4 m/s²

EASSM2310S

Carlo Gavazzi Timer Relays Timer On Delay 24 to 230V AC DC
Supply SCR Output 0.5 to 10 Seconds



MECHANICAL	Max. vibration frequency, operational	100 Hz
	Height	80 mm
DIMENSIONS	Depth	109 mm
	Width	22.5 mm
ENVIRONMENT	Operating temperature	-25...45 °C