# 193T1BC25

**Allen-Bradley 193T Overload Thermal 21 to 25A for 100C 30 and 37A**

MOTOR PROTECTION




| | |
|---|---|
| **Component type** | Thermal overload relay |
| **Range** | 193-T |
| **Model** | N/A |
| **Product status** | Existing |

The Allen-Bradley Bulletin 193-T1 IEC Bimetallic Overload Relays are motor protectors for IEC applications. Designed for use with Bulletin 100-C Contactors and Bulletin 104-C Reversing Contactors and feature adjustable trip settings, a manual reset button, and a differential mechanism for sensitivity to phase-loss conditions.

| | | |
|---|---|---|
| **ELECTRICAL** | Adjustable current range | 21-25 A |
| | Release class | CLASS 10 A |
| | Max. rated operation voltage Ue | 690 V |
| | Number of auxiliary contacts as normally closed contact | 1 |
| | Number of auxiliary contacts as normally open contact | 1 |
| | Reset function automatic | Yes |
| | Reset function push-button | Yes |
| | Type of electrical connection of main circuit | Screw connection |
| **CONSTRUCTION** | Mounting method | Direct attachment |
| **DIMENSIONS** | Height | 71.6 mm |
| | Width | 45 mm |
| | Depth | 63.5 mm |
| | Weight | 0.12 kg |



Published on 24 September 2026