

nVent HOFFMAN stainless steel

# Sloped roof wall mount enclosures

Specialised enclosures for protecting  
valuable equipment in mining and  
other dusty applications



[nhp.com.au](http://nhp.com.au) | [nhpnz.co.nz](http://nhpnz.co.nz)



1300 647 647 | 0800 647 647



[sales@nhp.com.au](mailto:sales@nhp.com.au) | [sales@nhp-nz.com](mailto:sales@nhp-nz.com)



nVent HOFFMAN stainless steel wall mount SRE enclosures are ideally suited for all mining applications.

## Robust design

- High impact resistance rating of IK10 - the highest possible
- IP66 ingress protection
- 38° sloped roof (the angle of repose for coal)
- High resistance to vandalism
- Folded and seam welded body
- Stainless steel concealed hinges with captive pin
- Marine grade 316L stainless steel for maximum corrosion resistance

## Innovative features

- Sloped roof prevents accumulation of liquids, dust and other debris
- Optional depth adjustment kit for mounting flexibility
- Flange top and bottom for easy mounting
- Easy to clean by hosing down in dusty and dirty locations
- White silicone gasket is UV and chemical resistant with almost zero water absorption
- Mounting plate supplied marked at 10mm increments for easy component layout
- Multiple earthing studs to simplify wiring and save time
- Four standard sizes to accommodate the majority of common applications
- Available in natural stainless steel and X1 orange finishes

Models shown below are supplied in an X15 orange powder coat finish

Enclosure dimensions (mm)								
Front H	W	D	Weight (kg)	Mounting plate height (mm)	Mounting plate width (mm)	Max. usable depth (mm)	Number of door locks	Catalogue no.
300	200	150	5	270	150	132	1	SRE0302015316X15
400	300	210	8	370	250	192	1	SRE0403021316X15
400	600	260	24	370	550	242	1	SRE0406026316X15
600	400	260	24	570	350	242	2	SRE0604026316X15
600	600	300	28	570	550	282	2	SRE0606030316X15
800	600	300	31	770	550	282	2	SRE0806030316X15
800	800	300	40	770	750	282	2	SRE0808030316X15
1000	800	300	55	970	750	282	1*	SRE1008030316X15

\*1000 mm high enclosures and above have espagnolette three point locking or 3 locks

#### Ordering information - Enclosures

Enclosure dimensions (mm)								
Front H	W	D	Weight (kg)	Mounting plate height (mm)	Mounting plate width (mm)	Max. usable depth (mm)	Number of door locks	Catalogue no.
300	200	150	5	270	150	132	1	SRE0302015316
400	300	210	8	370	250	192	1	SRE0403021316
400	400	210	12	370	350	192	1	SRE0404021316
400	600	260	24	370	550	242	1	SRE0406026316
600	400	260	24	570	550	282	2	SRE0604026316
600	600	210	26	570	550	192	2	SRE0606021316
600	600	300	28	570	550	282	2	SRE0606030316
800	600	300	31	770	550	282	2	SRE0806030316
800	800	300	40	770	750	282	2	SRE0808030316
1000	600	400	48	970	550	382	1*	SRE1006040316
1000	800	300	55	970	750	282	1*	SRE1008030316

\*1000 mm high enclosures and above have espagnolette three point locking or 3 locks

**Models shown below are supplied in an X15 orange powder coat finish**

Enclosure dimensions (mm)		Inner doors*	Glazed doors*	Modular chassis*	Interior mounting profiles*	Depth adjustment*	Document holder*	Door switch*	Enclosure lights*	Filter fans / filter grilles*	Pressure compensation /drainage devices*	Catalogue no.
AD104030R5	ADCS04030316	-	-	AMTExxxx	-	-	-	-	E21407SS, GSV10002xx / GSF10	28402001	SRE0302015316	
AD104030R5	ADIS04030	AC04030R5	MMDP040 DIP210	AMTExxxx AMG210	DRB0303R5 DRA4	ADSW01	LED0254xxxx TL40014W	DD084 DA28404000	E214xxSS, GSVxx / GSFxx EFCSxxx	28402001	DA28455	
AD106040R5	ADCS06040316	AC06040R5	MMDP060 DIP260 CLPK400 CLPK600 CLPF400 CLPF600	AMTExxxx, AMG260	DRB0303R5 DRA4	ADSW01	LED0254xxxx TL40014 TLCL87035	DD084	E214xxSS, GSVxx / GSFxx EFCSxxx	28402001	DA28455	
AD108060R5	ADCS08060316	AC08060R5	MMDP080 DIP300 CLPK600 CLPK800 CLPF600 CLPF800	AMTExxxx, AMG300	DRB600R5 DRB0303R5 DRA4	ADSW01	LED0254xxxx TL40014W TLCL87035	DD084	E214xxSS, GSVxx / GSFxx EFCSxxx	28402001	DA28455	
AD108060R5	ADCS08060316	AC08060R5	-	-	AMTExxxx	-	-	-	E21407SS GSV10002xx / GSF10	28402001	DA28455	
AD104030R5	ADCS04030316	-	MMDP040 DIP210 CLPK400 CLPK600 CLPF600	AMTExxxx AMG210	DRB0303R5 DRA4	ADSW01	LED0254xxxx TL40014W	DD084	E214xxSS, GSVxx / GSFxx EFCSxxx	28402001	DA28455	
AD106040R5	ADCS06040316	AC06040R5	MMDP060 DIP260 CLPK400 CLPK600 CLPF400 CLPF600	AMTExxxx, AMG260	DRB0303R5 DRA4	ADSW01	LED0254xxxx TL40014W TLCL87035	DD084	E214xxSS, GSVxx / GSFxx EFCSxxx	28402001	DA28455	
AD108060R5	ADCS08060316	AC08060R5	MMDP080 DIP300 CLPK600 CLPK800 CLPF600 CLPF800	AMTExxxx, AMG300	DRB600R5 DRB0303R5 DRA4	ADSW01	LED0254xxxx TL40014W TLCL87035	DD084	E214xxSS, GSVxx / GSFxx EFCSxxx	28402001	DA28455	
AD108060R5	ADCS08060316	AC08060R5	-	-	-	-	-	-	E214xxSS, GSVxx / GSFxx EFCSxxx	28402001	DA28455	

# Accessories for nVent HOFFMAN stainless steel SRE wall mount enclosures

There are many accessories available for nVent HOFFMAN stainless steel wall mount enclosures which are discussed in detail below. Due to the large number, the accessories have been grouped into the following categories:



## Internal

- This includes inner doors, door stops, door hinges, glazed doors, mounting profiles and document holders

## 19" rack mounting

- Covers the range of 19" rack mount options, including brackets and profiles



## Lighting

- Covers enclosure LED lighting options

## Climate control

- This includes filter fans and grilles, fan hoods and pressure compensation devices

# Internal accessories

This section includes all internal mounting accessories such as inner doors, mounting profiles, separation plates and brackets EXCEPT 19" rack equipment (separate section).



## Inner doors for wall mount enclosures, ADIxxxxR5, ADISxxxx

ADI inner doors provide a hinged mounting surface for equipment such as displays, indicators or switches behind a standard or glazed front door, while covering other components and preventing unauthorised access. A usable mounting space of 35 mm is available between the doors when the inner door is in the forwardmost position.

**Description** Can be adjusted in depth with the AMG Depth Adjustment Kit. The inner door is equipped with one (H<700mm) or two (H700mm and higher ADI, H800mm and higher ADIS) double-bit 3 mm locks. ADI/ADIS inner doors are compatible with both mild steel and stainless steel enclosures and provide an IP2X protection rating. Supplied with two vertical profiles, top and bottom profiles and mounting accessories.

Note: machining is required to install the inner door

<b>Ordering information</b>	ADI04030R5 ADI06040R5 ADI08060R5	Mild steel powder coated inner doors Inner door, H400 x W300mm Inner door, H600 x W400mm Inner door, H800 x W600mm
<b>Material</b>	ADI: mild steel 1.5mm, 2mm top and bottom profiles, RAL 7035 structured powder coating ADIS: AISI 304 stainless steel 1.5mm door, 2mm top and bottom profiles 400 pre-grained finish	

## Door stop, ADO202



ADO door stop can be easily mounted on site and prevents the door from closing unexpectedly, thus increasing operator safety. Available in both zinc plated and stainless steel variants, the ADO is supplied with mounting accessories.

Note – ADO door stops cannot be used on enclosures with a width of less than 300mm.

<b>Ordering information</b>	ADO202 ADO202S	Door stop in zinc plated steel, supplied with mounting accessories Door stop in stainless steel, supplied with mounting accessories
<b>Material</b>	ADI: mild steel 1.5mm, 2mm top and bottom profiles, RAL 7035 structured powder coating ADIS: AISI 304 stainless steel 1.5mm door, 2mm top and bottom profiles 400 pre-grained finish	

## Glazed doors for wall mount enclosures, ADCSxxxx



### Description

ADCS glazed doors provide a hinged mounting surface for equipment such as displays, indicators or switches behind a standard or glazed front door, while covering other components and preventing unauthorised access. A mounting space of 80mm is available between the doors when the inner door is in the most forward position. Can be adjusted in depth by steps of 25mm.

### Ordering information

ADCS04030316 Glazed door, H400 x W300mm  
ADCS06040316 Glazed door, H600 x W400mm  
ADCS08060316 Glazed door, H800 x W600mm

Note: other sizes are available on request, however a longer lead-time and minimum order quantity may apply. Please contact NHP with your query.

### Material

1.5mm 316L stainless with 400 pre-grained finish

## Modular chassis, ACxxxx



### Description

AC modular chassis allows DIN rail components to be mounted quickly and easily. Maximum component height is 68mm and row spacing is 125mm. If required, the standard door can be replaced with a glazed door. The usable depth between the front cover and external door is 35mm. Supplied as a kit with slotted front panel, two vertical profiles, top and bottom blank panels, one DIN rail per row and mounting accessories. Machining is required to install the AC modular chassis.

### Ordering information

ACO4030R5 Modular chassis, H400 x W300mm  
ACO6040R5 Modular chassis, H600 x W400mm  
ACO8060R5 Modular chassis, H800 x W600mm

### Material

DIN rails made of 1.2mm galvanised steel, vertical profiles and strong cover made of 1.5mm mild steel, RAL 7035 structured powder coat finish

## Door mounting profiles, MMDPxxxx



### Description

MMDP mounting profiles provide additional stiffness to the enclosure door and allow electrical components and other accessories to be mounted easily on the door. MMDP are supplied as a pair with mounting accessories.

### Ordering information

MMDP040 Door mounting profiles, H400mm, set of 2  
MMDP060 Door mounting profiles, H600mm, set of 2  
MMDP080 Door mounting profiles, H800mm, set of 2

### Material

1.2mm galvanised steel

## Depth interior profiles, DIPxxx



### Description

The DIP (depth interior profile system) is a 40mm wide and 25mm high mounting profile which can be mounted on the enclosure depth. It can also be used in conjunction with CLPF profiles, providing flexibility for the mounting of accessories, components and other equipment such as enclosure lights. Two rows of hole patterns for cage nut fixing and self-tapping screws are provided. Supplied as a set of 4 with mounting accessories.

Note: DIP depth interior profiles cannot be used in conjunction with the AMG depth adjustment kit


### Ordering information

DIP210	Depth interior profile 210mm, 150N max loading, set of 4
DIP260	Depth interior profile 260mm, 150N max loading, set of 4
DIP300	Depth interior profile 300mm, 150N max loading, set of 4

### Material

Zinc plated steel

## Click-in mounting profiles, CLPKxxx



### Description

CLPK click-in mounting profiles allow additional accessories and equipment to be easily mounted where needed. This 75mm wide profile has three sets of holes, one of which is turned 90°, allowing the CLPK to be mounted in both horizontal and vertical directions. Supplied as a set of 4 with mounting accessories.

Note: CLPK profiles require DIP profiles to be installed first and are not suited to smaller ASR sizes. Please observe maximum loading of the DIP.


### Ordering information

CLPK400	click-in profile W/D 400mm, set of 4
CLPK600	click-in profile W/D 600mm, set of 4
CLPK800	click-in profile W/D 800mm, set of 4

### Material

1.5mm zinc plated steel

## Mounting profiles, Snapline CLPFxxx



### Description

The CLPF profile system is a 40mm wide and 25mm high mounting profile which can be mounted in all directions when used together with the DIP accessory, providing full flexibility for the mounting of accessories, components and other equipment. Two rows of hole patterns for cage nut fixing and self-tapping screws are provided. The CLPF is a Snapline accessory and can be quickly and easily installed without any tools. All CLPF profiles are supplied as a set of 4. CLPK profiles require DIP profiles to be installed first.

Please observe maximum loading of the DIP.

### Ordering information

CLPF300	Snapline mounting profile W/D 300mm, set of 4
CLPF400	Snapline mounting profile W/D 400mm, set of 4
CLPF600	Snapline mounting profile W/D 600mm, set of 4

### Material

Zinc plated steel



### Depth adjustment kit, AMGxxx

<b>Description</b>	AMG depth adjustment kits allow the mounting plate, 19" profiles or an inner door to be mounted at various depths within the enclosure from 35 to 65mm from the door. AMG is supplied as two pairs with mounting accessories. Machining is required.
<small>Note: the AMG depth adjustment kit cannot be used in conjunction with DIP depth interior profiles</small>	
<b>Ordering information</b>	AMG210 depth adjustment kit D210mm AMG260 depth adjustment kit D260mm AMG300 depth adjustment kit D300m
<b>Material</b>	2mm galvanised steel



### Depth adjustment bolts, AMTExxx

<b>Description</b>	AMTE depth adjustment (spacer) bolts are an economical solution to mount the mounting plate at various depths within the enclosure, adjustment steps from 10mm to 100mm. The spacer bolts are supplied in packs of 20 or 50, depending on size.
<b>Ordering information</b>	AMTE8010 Spacer bolts m8, 10mm, qty 50 AMTE8020 Spacer bolts m8, 20mm, qty 50 AMTE8030 Spacer bolts m8, 30mm, qty 50 AMTE8040 Spacer bolts m8, 40mm, qty 20 AMTE8050 Spacer bolts m8, 50mm, qty 20 AMTE8055 Spacer bolts m8, 55mm, qty 20 AMTE8100 Spacer bolts m8, 100mm, qty 20
<b>Material</b>	Zinc plated steel



### Document holders DRA4, DRBxxxR5

<b>Description</b>	Document holders can be mounted in the enclosure to ensure that the required documents are readily available.
<b>Description</b>	The DRA4 document pocket, with a usable depth of 30mm suits documents up to A4 in size and is made from polymer and attaches easily with double sided tape.
<b>Ordering information</b>	DRA4 Self-adhesive document pocket A4 DRB03030R5 Universal document pocket 300mm wide DRB600R5 Document pocket for w600mm doors
<b>Material</b>	DRA4 thermoplastic, RAL 7035 DRBxxxxR5 2mm zinc plated steel with RAL 7035 structured powder coating

The background image is an aerial photograph of a large-scale mining operation. The site features several dirt roads winding through a landscape of exposed rock and earth. The rock faces are particularly striking, displaying a vibrant palette of reds, oranges, yellows, and browns, likely due to mineral content or weathering. Some areas show signs of active mining, while others are more like graded roads or open pits. The overall scene conveys a sense of industrial activity and the scale of natural resources extraction.

Mining and other dusty applications

# Protecting valuable equipment

# Enclosure lighting

This section provides a high-level overview of the enclosure lighting options available.

## Door switch ADSW01



### Description

ADSW01 door switches allow lights or other electrical devices to turn on or off automatically when the enclosure door is opened. They include a NO (normally open) and one NC (normally closed), volt-free contact. Designed to be mounted directly to the enclosure frame. The mounting locations ensure that the switch is always positioned for correct operation once installed.

Note: machining is required to install the ADSW01

### Ordering information

ADSW01

Door switch 3A / 240V, supplied with mounting accessories

### Material

Polymer body

## Enclosure lights, LED025xxxx



### Description

LED 025 enclosure lights, manufactured by Stego, are suitable for all enclosures. They are available in 100-240V AC and 24-48V DC versions in both screw mount and magnet mount. With 400 lumens, 120° illumination angle and daylight white (6000K) colour, they provide good illumination inside the enclosure.

Please contact NHP for additional information and other options.

### Ordering information

LED02540001

LED 025 lamp 5W/400Lm 100-240V AC, screw mount, ON/OFF switch, supplied with connector

LED02540101

LED 025 lamp 5W 24-48V DC, screw mount, motion detector, supplied with connector

### Material

Transparent plastic housing

# Climate control

This section provides a high-level overview of the climate control options available. Please refer to the Climate Control Selection Guide or contact NHP for more details.

## Fan covers, EFCSxxxx



### Description

EFCS fan covers feature a sloped roof and prevent rain and water in hose-down applications hitting the filter fan or filter grille. Supplied with mounting accessories. Made from 316 grade stainless steel, are compatible with both mild and stainless steel enclosures and should always be used where the enclosure is likely to be exposed to rain or hose-down cleaning. The EFCS is available in three sizes to suit different sizes of the GSV filter fans and GSF filter grilles.

Note: EFCS is not suitable for the SRE0302015316 due to depth

### Ordering information

EFCS20316	Fan cover h275 x w175 x d100mm, suits gsv1000, gsf10 sizes
EFCS2530316	Fan cover h375 x w275 x d100mm, suits gsv1500, gsf2000, gsv2500, gsf15, gsf20 and gsf25 sizes

### Material

1.5mm 316 grade stainless steel

## Filter fans GSVxxxx and filter grilles GSFxx



### Description

Kryos3 GSV filter fans and GSF filter grilles, manufactured by Cosmotec, are easy to install with clip-on mounting. GSV filter fans have efficient filter mats, screwless terminals, long life ball bearing fans and have a reversible fan motor for air in or air out. Available in a range of sizes and air flows, they are suitable for all floor standing enclosures and have IP54 protection. They can be used both indoors and outdoors, however a suitable EFCS fan cover should be installed in locations where inclement weather, or hose-down cleaning may occur.

Replacement filter mats are available.

For more information on the GSV/GSF range, please refer to the Climate Control Selection Guide and Price List Catalogue.

### Ordering information

GSV1000211	Filter fan h119 x w119 x d58mm 24v dc 35m3/hr
GSV1000220	Filter fan h119 x w119 x d58mm 230v ac 35m3/hr
GSV1500211	Filter fan h152 x w152 x d75mm 24v dc 67m3/hr
GSV1500220	Filter fan h152 x w152 x d75mm 230v ac 67m3/hr
GSV2000211	Filter fan h204 x w204 x d98mm 24v dc 108m3/hr
GSV2000220	Filter fan h204 x w204 x d98mm 230v ac 108m3/hr
GSV2500211	Filter fan h250 x w250 x d118mm 24v dc 190m3/hr
GSV2500220	Filter fan h250 x w250 x d118mm 230v ac 190m3/hr
GSV2501220	Filter fan h250 x w250 x d99mm 230v ac 270m3/hr

### Material

1.5mm 316 grade stainless steel



## Filter fans GSVxxxx and filter grilles GSFxx

Ordering information	Filter grilles	
	GSF10	Filter grille H119 x W119 x D29mm GSF15
Ordering information	GSF25	Filter grille H152 x W152 x D33mm GSF20
		Filter grille H204 x W204 x D34mm
Ordering information	Replacement filter mats	Filter grille H250 x W250 x D48mm
	AVAFAGS10	Replacement filter mat IP54 suits GSV1000, GSF10, pack of 10
Ordering information	AVAFAGS15	Replacement filter mat IP54 suits GSV1500, GSF15, pack of 10
	AVAFAGS20	Replacement filter mat IP54 suits GSV2000, GSF20, pack of 10
Ordering information	AVAFAGS25	Replacement filter mat IP54 suits GSV2500, GSF25, pack of 10
Material	Filter fan and filter grille body, ABS filter mat, synthetic fibre	



## Pressure compensation devices, DA284xx

### Description

DA284 pressure compensation devices, manufactured by Stego, are easy to install and provide effective pressure equalisation between the inside and outside of the enclosure.

The one-way membrane allows moisture to escape while preventing the ingress of liquid, dirt and debris. AS3000:2018 clause 1.7.2 states that "a breathing/pressure equalization valve shall be installed to assist with changes in humidity and drainage of moisture". Therefore, to comply with the new AS3000:2018 standards, pressure compensation devices must be fitted to all enclosures where condensation is likely to occur - in practice, all enclosures installed outdoors.

Pressure compensation devices should always be installed in pairs on opposite sides of the enclosure. The Stego DA284 is available in stainless steel and has an ingress protection rating of IP66 according to EN 60259 and IP69K according to EN 400050-9.

Ordering information	28402001	Pressure compensation device, aisi 303 grade stainless steel, m12 ip66/x9k (qty 1)
	DA28455	Pressure compensation device, aisi 303 grade stainless steel, m40 ip66/x9k (qty 1)
	DA28404000	Pressure compensation device, nickel-plated aluminium, m12, ip67 (qty 1)
Material	303 or 316L grade stainless steel, or nickel-plated aluminium, model dependent	

## Drainage device, DD084

### Description

DD084 drainage devices, manufactured by Stego, are easy to install and provide effective drainage of any condensation at the bottom of the enclosure. The one-way membrane allows up to 200ml/h of liquid to escape while preventing the ingress preventing the ingress of liquid, dirt and debris.

### Ordering information

DD084	Drainage device, plastic, m50 ip66/x9k (qty 1)
Material	Grey UV resistant plastic (UL746C), NBR sealing gasket



# Key benefits

The nVent HOFFMAN SRE range offers several key benefits

- Available in a four standard sizes ex-stock, minimising delivery time
- Available in natural brushed stainless steel finish and in X15 orange powder coat finish
- The silicone gasket has virtually zero water absorption and when compared to a traditional polyurethane gasket, has better UV and chemical resistance and a wider temperature range
- Earthing studs provided on enclosure body and door, thus simplifying the wiring and reducing wiring time
- The SRE range is built on the same platform as the existing nVent HOFFMAN mild steel and stainless steel enclosures, ensuring compatibility with existing accessories such as inner doors and depth adjustment kits
- The supplied mounting plate is pre-marked at 10mm increments, making it easier to align, mount and remove components
- Easy depth adjustment provides the flexibility to suit different depth components
- An integrated rain hood with 20mm overhang provides additional protection to the internal components
- The hinges are designed for easy removal and reversible for right or left hand opening
- The 38° sloped roof design is self draining, preventing the accumulation of dust or debris

## Integrated wall brackets

- Mounting flange top and bottom
- No drilling required
- Faster installation
- Mounting holes outside ingress protected area



## Locks

- Range of locking options
- Refer to the table on page 3

## Applications

The nVent HOFFMAN SRE range has been designed with cleanliness and ingress protection in mind and provides high resistance to corrosion. The innovative design of the sloped roof facilitates easy cleaning and ensures that debris and potentially hazardous dust cannot accumulate - critical for mining applications. Intended for dusty environments, the SRE range is ideally suited to applications in the following industries and environments:

- Mining
- Water and wastewater treatment plants
- Marine environments
- Renewable energy
- Heavy industry
- Other dusty environments such as quarries and cement plants



### Mounting plate

- Supplied with enclosure
- Pre-marked at 10mm intervals
- Galvanised steel 2mm thick

### Multiple earthing studs

- In the door
- In the enclosure
- Simplifies wiring

### Depth adjustment kit

- Optional accessory
- Easy to fit and adjust
- Flexibility for various depth components



[nhp.com.au](http://nhp.com.au)  
1300 647 647  
[sales@nhp.com.au](mailto:sales@nhp.com.au)

[nhpnz.co.nz](http://nhpnz.co.nz)  
0800 647 647  
[sales@nhp-nz.com](mailto:sales@nhp-nz.com)

**NHP Electrical Engineering Products**

A.B.N. 84 004 304 812

©NHP 2025

16BCH 03/25