100SE09EJ23C

Allen-Bradley 100SE Safety Contactor 4kW 3P 24-60V AC/DC Coil 2NO 3NC Auxiliary

CONTACTORS



Component type	Power contactor, AC switching
Range	100SE
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 100S-E safety contactors provide mechanically linked positively guided or mirror contact performance, required in the feedback circuits of modern safety applications.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation power at AC-3, 400 V	4 kW
	Max. rated operation voltage Ue AC	690 V
	Voltage type for actuating	AC/DC
	Rated control supply voltage Us at AC 50HZ	24-60 V
	Rated control supply voltage Us at DC	24-60 V
	Number of auxiliary contacts as normally open contact	2
	Number of auxiliary contacts as normally closed contact	3
	Rated operation power at AC-3, 690 V	5.5 kW
	Rated control supply voltage Us at AC 60HZ	24-60 V
	Type of electrical connection of main circuit	Screw connection
CONSTRUCTION	IP rating	IP20
	Mounting method	DIN-rail/screw
DIMENSIONS	Height	86 mm
	Width	45 mm
	Depth	110.5 mm
	Weight	0.87 kg

Published on 06 November 2026