20G11ND027JA0NNNNN

Allen-Bradley PowerFlex 755 VSD 480V IP20 ND 27A 20HP or 22A 15HP Frame 3

LARGE DRIVES



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755
Model	N/A
Product status	Existing

Allen-Bradley PowerFlex 755 AC Drives are a simple and high-performance motor control application, providing a variety of solutions including pumps, fans, and conveyors. Featuring a standard built-in Ethernet/IP port, making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware. and safety options.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	480 V
	Nominal output power AC	500 kW
	Nominal output current I2N	27 A
CONSTRUCTION	Suitable for safety functions	Yes
	Frame size	3
	IP rating	IP20
DIMENSIONS	Height	454 mm
	Width	190 mm
	Depth	212 mm
ENVIRONMENT	Storage temperature	-40…70 °C

Published on 29 October 2026


20G11ND027JA0NNNNN

Allen-Bradley PowerFlex 755 VSD 480V IP20 ND 27A 20HP or 22A 15HP Frame 3

LARGE DRIVES

NHP Allen-Bradley

DIMENSIONAL DIAGRAM



Dimensions are in millimeters and (inches).
Weights are in kilograms and (pounds).

Frame	A	B	C	D	E	F	Weight, kg (lb)
1	110.0 (4.33)	400.5 (15.77)	211.0 (8.31)	68.0 (2.68)	82.0 (3.23)	390.4 (15.37)	6.0 (12.75)
2	134.5 (5.30)	424.2 (16.70)	212.0 (8.35)	100.0 (3.94)	100.0 (3.94)	404.2 (15.91)	7.8 (17.2)
3	190.0 (7.48)	454.0 (17.87)	212.0 (8.35)	158.0 (6.22)	158.0 (6.22)	435.0 (17.13)	11.8 (26.1)
4	222.0 (8.74)	474.0 (18.66)	212.0 (8.35)	194.0 (7.64)	202.0 (7.95)	455.0 (17.91)	13.6 (30.0)
5	270.0 (10.63)	550.0 (21.65)	212.0 (8.35)	238.0 (9.37)	238.0 (9.37)	531.0 (20.91)	20.4 (45.0)

Published on 29 October 2026