
20GE1GC037JA0NNNNN

Allen-Bradley PowerFlex 755TS VSD XT 400V IP54 ND 37A 18.5kW or HD 30A 15kW Frame 3

LARGE DRIVES



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755TS
Model	N/A
Product status	Existing

The Allen-Bradley PowerFlex 755TS Low Voltage AC drives are the next generation optimised range of drives in the 750 series. Fitted with TotalFORCE technology delivering high performance motor control, predictive analytics and real-time operational intelligence, increasing productivity and uptime while reducing energy and maintenance costs.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	400 V
	Nominal output power AC	30 kW
	Nominal output current I2N	37 A
	kW rating, normal duty	18.5 kW
	kW rating, heavy duty	15 kW
CONSTRUCTION	Suitable for safety functions	Yes
	Frame size	3
	IP rating	IP54
DIMENSIONS	Height	454 mm
	Width	190 mm
	Depth	212 mm
ENVIRONMENT	Storage temperature	-40…70 °C


Published on 05 November 2026

20GE1GC037JA0NNNNN

Allen-Bradley PowerFlex 755TS VSD XT 400V IP54 ND 37A 18.5kW or HD 30A 15kW Frame 3

LARGE DRIVES

DIMENSIONAL DIAGRAM



Dimensions are in millimeters and (inches).
Weights are in kilograms and (pounds).

Frame	A	B	C	D	E	Weight, kg (lb)
2	215.3 (8.48)	543.2 (21.39)	222.2 (8.75)	100.0 (3.94)	528.2 (20.80)	7.8 (17.2)
3	268.0 (10.55)	551.0 (21.69)	220.1 (8.67)	158.0 (6.22)	533.0 (20.98)	11.8 (26.1)
4	300.0 (11.81)	571.0 (22.48)	220.1 (8.67)	194.0 (7.64)	553.0 (21.77)	13.6 (30.0)
5	348.0 (13.70)	647.0 (25.47)	220.1 (8.67)	238.0 (9.37)	629.0 (24.76)	20.4 (45.0)

Published on 05 November 2026