ISO440PYCOS

Socomec ISO Enclosed Changeover Switch IP 65 Polycarbonate Red and Yellow Handle 4Pole 40A

ENCLOSED ISOLATORS

Component type	Switch disconnector
Range	COMO Changeover
Model	N/A
Product status	Existing

ELECTRICAL	Max. rated operation voltage Ue AC	690 V
	Rated permanent current at AC-21, 400 V	40 A
	Rated uninterrupted current Iu	40 A
	Number of poles	4
	Rated operation power at AC-23, 400 V	11 kW
	Rated impulse withstand voltage Uimp	6 kV
	Type of control element	Door coupling rotary drive
	Type of electrical connection of main circuit	Cable clamp
	Rated operating voltage	690 V
	Rated permanent current at AC-23, 400 V	29 A
	Switching power at 400 V	11 kW
	Number of auxiliary contacts as normally closed contact	0
	Number of auxiliary contacts as normally open contact	0
	Number of auxiliary contacts as change-over contact	0
	Motor drive optional	No
	Motor drive integrated	No
	Voltage release optional	No
CONSTRUCTION	Device construction	Complete device in housing
	Colour control element	Black
	Degree of protection (IP), front side	IP65
	Degree of protection (NEMA)	4X
	Version as main switch	Yes
	Version as maintenance-/service switch	Yes
	Version as safety switch	Yes

Published on 24 August 2026

ISO440PYCOS

Socomec ISO Enclosed Changeover Switch IP 65 Polycarbonate Red and Yellow Handle 4Pole 40A

ENCLOSED ISOLATORS

CONSTRUCTION	Version as emergency stop installation	No
	Version as reversing switch	No
	Number of switches	2
	Suitable for front mounting 4-hole	Yes
	Suitable for front mounting centre	No
	Suitable for distribution board installation	No
	Suitable for intermediate mounting	No
	Interlockable	Yes
MECHANICAL	Padlock locking	Yes
DIMENSIONS	Height	200 mm
	Width	146 mm
	Depth	138 mm

Published on 24 August 2026