


DIN-T high current MCBs

Commercial and industrial protection

- AS/NZS 60947-2
- 50kA short circuit rating
- 80A, 100A and 125A
- 1P, 2P, 3P and 4P
- B, C and D trip curves



nhp.com.au | nhpnz.co.nz



1300 647 647 | 0800 647 647




sales@nhp.com.au | sales@nhp-nz.com


New and improved DIN-T 10H range with improved ratings

The new DIN-T 10H MCB now offers an impressive 50kA short circuit rating to AS/NZS60947-2. The DIN-T 10H MCB comes complete with 2 arcing chambers per pole, which offers excellent operating characteristics. High fault levels AS/NZS60947-2 Icu 50kA and Ics 40kA.

Due to the fast operating time of <2.5ms, the DIN-T10H MCB offers good selectivity with upstream protection devices and limits damage downstream with limited let-through energy. Suitable for voltages 12V AC/DC through to 500V AC/DC. Suits NCH busbar chassis with 27mm.




Part number conversion



Accessories



Dimensions



* 125A has 4.5mm side covers, remove when fitting beside MCB or fitting a side mount accessory

Locking devices



Description	Fitting	Catalogue no.
Shunt trip 220-415 V AC	LH side only	DTMHSHT220415
Shunt Trip 48-130 V AC	LH side only	DTMHSHT48130
Auxiliary and alarm C/O contact	LH side only	DTMHAUXAL
IP20 terminal shroud	Bottom terminal (required when not chassis mounted for IP20)	DTMHSRD
Side mount locking device	RH side only (padlock not included)	DTMHL D
Removable locking device	Front mount	DTMHL DNC
LOCKDIN	Bottom	DTALMH