

ISO340PYCOS

Socomec ISO Enclosed Changeover Switch IP 65
Polycarbonate Red and Yellow Handle 3Pole 40A



ENCLOSED ISOLATORS

socomec
Innovative Power Solutions



Component type	Switch disconnecter
Range	COMO Changeover
Model	N/A
Product status	Existing

ELECTRICAL

Max. rated operation voltage Ue AC	690 V
Rated permanent current at AC-21, 400 V	40 A
Rated uninterrupted current Iu	40 A
Number of poles	3
Rated operation power at AC-23, 400 V	11 kW
Type of control element	Door coupling rotary drive
Type of electrical connection of main circuit	Cable clamp
Rated operating voltage	690 V
Rated permanent current at AC-23, 400 V	29 A
Switching power at 400 V	11 kW
Conditioned rated short-circuit current Iq	50 kA
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No

CONSTRUCTION

Device construction	Complete device in housing
Colour control element	Black
Degree of protection (IP), front side	IP65
Degree of protection (NEMA)	4X
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes

ISO340PYCOS

Socomec ISO Enclosed Changeover Switch IP 65
Polycarbonate Red and Yellow Handle 3Pole 40A



ENCLOSED ISOLATORS



CONSTRUCTION	Version as emergency stop installation	No
	Version as reversing switch	No
	Number of switches	1
	Suitable for front mounting 4-hole	Yes
	Suitable for front mounting centre	No
	Suitable for distribution board installation	No
	Suitable for intermediate mounting	No
	Interlockable	Yes
MECHANICAL	Padlock locking	Yes
DIMENSIONS	Height	200 mm
	Width	146 mm
	Depth	138 mm