100KFA20E

Allen-Bradley 100K Auxiliary Contact with 2NO Contacts Front Mount for 100K and 700K

CONTACTORS

NHP | Allen-Bradley



Component type	Auxiliary contact block
Range	100K
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 100-K miniature contactors are ideal for commercial and light industrial applications where panel space is at a premium. Measuring only 45 mm wide, they are shallower and have less panel depth requirements than standard IEC contactors.

ELECTRICAL	Number of contacts as normally open contact	2
	Rated insulation voltage Ui	690 V
	Rated operation current Ie at AC-15, 24 V	3 A
	Rated operation current Ie at AC-15, 120 V	3 A
	Rated operation current Ie at AC-15, 240 V	2 A
	Rated operation current Ie at AC-15, 400 V	1.2 A
	Rated operation current Ie at DC-13, 24 V	2.3 A
	Rated operation current Ie at DC-13, 110 V	0.55 A
	Rated operation current Ie at DC-13, 220 V	0.27 A
	Min. contact rating current	2 mA
	Min. contact rating voltage	15 V
	Rated operation current Ie at AC-15, 230 V	2 A
CONSTRUCTION	Mounting method	Top mounting

Published on 30 September 2026