
100SE205KN12C

Allen-Bradley 100SE Safety Contactor 110kW 3Pole 250 to 500VAC and VDC Coil 1NO 1NC Contact Aux

SAFETY CONTACTORS



Component type	Power contactor, AC switching
Range	100SE
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 100S-E safety contactors provide mechanically linked positively guided or mirror contact performance, required in the feedback circuits of modern safety applications.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation current Ie at AC-3, 400 V	205 A
	Rated operation power at AC-3, 400 V	110 kW
	Rated operation current Ie at AC-1, 400 V	350 A
	Max. rated operation voltage Ue AC	1000 V
	Voltage type for actuating	AC/DC
	Rated control supply voltage Us at AC 50HZ	250-500 V
	Rated control supply voltage Us at DC	250-500 V
	Number of auxiliary contacts as normally open contact	1
	Number of auxiliary contacts as normally closed contact	2
	Rated operation current Ie at AC-3, 690 V	165 A
	Rated operation power at AC-3, 690 V	160 kW
	Rated operation current Ie at AC-3, 1000 V	100 A
	Rated operation power at AC-3, 1000 V	132 kW
	Rated operation power at AC-4, 400 V	80 kW
	Rated control supply voltage Us at AC 60HZ	250-500 V
	Power consumption, AC coil pickup	205 VA
	Power consumption, AC coil hold-in	16 VA
	Power consumption, DC coil pickup	190 W
	Power consumption, DC coil hold-in	4 W
	Type of electrical connection of main circuit	Bolt connection
	Rated operation current Ie at AC-4, 400 V	156 A
CONSTRUCTION	IP rating	IP00

Published on 02 October 2026


100SE205KN12C

Allen-Bradley 100SE Safety Contactor 110kW 3Pole 250 to 500VAC and VDC Coil 1NO 1NC Contact Aux

SAFETY CONTACTORS

CONSTRUCTION	Mounting method	Screw mounting
DIMENSIONS	Height	196 mm
	Width	105 mm
	Depth	152 mm
	Weight	3 kg

DIMENSIONAL DIAGRAM



Dimensions are shown in millimeters (inches).

Published on 02 October 2026