
100SE305KY12C

Allen-Bradley 100SE Safety Contactor 160kW 3Pole 48 to 130VAC and VDC Coil 1NO 1NC Contact Auxiliary

SAFETY CONTACTORS

NHP Allen-Bradley



Component type	Power contactor, AC switching
Range	100SE
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 100S-E safety contactors provide mechanically linked positively guided or mirror contact performance, required in the feedback circuits of modern safety applications.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation current Ie at AC-3, 400 V	305 A
	Rated operation power at AC-3, 400 V	160 kW
	Rated operation current Ie at AC-1, 400 V	500 A
	Max. rated operation voltage Ue AC	1000 V
	Voltage type for actuating	AC/DC
	Rated control supply voltage Us at AC 50HZ	48-130 V
	Rated control supply voltage Us at DC	48-130 V
	Number of auxiliary contacts as normally open contact	1
	Number of auxiliary contacts as normally closed contact	2
	Rated operation current Ie at AC-3, 690 V	290 A
	Rated operation power at AC-3, 690 V	250 kW
	Rated operation current Ie at AC-3, 1000 V	131 A
	Rated operation power at AC-3, 1000 V	185 kW
	Rated operation power at AC-4, 400 V	132 kW
	Rated control supply voltage Us at AC 60HZ	48-130 V
	Power consumption, AC coil pickup	340 VA
	Power consumption, AC coil hold-in	17 VA
	Power consumption, DC coil pickup	360 W
	Power consumption, DC coil hold-in	2.5 W
	Type of electrical connection of main circuit	Bolt connection
	Rated operation current Ie at AC-4, 400 V	230 A
CONSTRUCTION	IP rating	IP00

Published on 02 October 2026


100SE305KY12C

Allen-Bradley 100SE Safety Contactor 160kW 3Pole 48 to 130VAC and VDC Coil 1NO 1NC Contact Auxiliary

SAFETY CONTACTORS

CONSTRUCTION	**Mounting method**	Screw mounting
DIMENSIONS	**Height**	225 mm
	Width	140 mm
	Depth	180 mm
	Weight	4.64 kg

DIMENSIONAL DIAGRAM



Dimensions are shown in millimeters (inches).

Published on 02 October 2026