# 140GH0C4C16

**Allen-Bradley 140G MCCB H Frame 120kA 4P 16A Fixed Thermal Magnetic**




| | |
|---|---|
| **Component type** | Power switching circuit breaker |
| **Range** | Moulded Case Circuit Breaker |
| **Model** | N/A |
| **Product status** | Existing |

The Allen Bradley motor protection circuit breakers offer a reliable solution with both short-circuit and overload protection for individual motor loads with high interrupt ratings for 2 and 3 pole devices. Ideal for motor starting and motor protection applications. Connecting modules are available and have been combination short-circuit tested with the Allen Bradley 100-E contactors.

| | | |
|---|---|---|
| **ELECTRICAL** | Rated current In | 16 A |
| | Number of poles | 4 |
| | Max. rated operation voltage Ue AC | 690 V |
| | Rated ultimate short-circuit breaking capacity Icu at 415 V, 50 Hz | 120 kA |
| | Type of protection trip unit | Thermal/magnetic release |
| | Trip curve | Fixed thermal, fixed magnetic |
| | Frame size rating | 160 A |
| | Rated frequency | 50-60 Hz |
| | Rated insulation voltage Ui | 1000 V |
| | Suitable for isolation | Yes |
| | Rated short circuit breaking capacity, Icu 690V AC | 18 kA |
| | Rated short circuit breaking capacity, Ics 690V AC | 13.5 kA |
| | Rated impulse withstand voltage Uimp | 8 kV |
| | Reverse connection of supply possible | Yes |
| | Electrical life at Un, In (service cycles) | 8000 cycles |
| | Power loss | 5.2 W |
| **MECHANICAL** | DIN rail (top hat rail) mounting optional | Yes |
| | Mechanical life (service cycles) | 25000 cycles |
| **DIMENSIONS** | Height | 130 mm |
| | Width | 120 mm |
| | Pole connection pitch | 30 mm |
| | Built-in depth | 82.5 mm |
| | Depth (toggle included) | 116 mm |
| | Weight | 1.6 kg |



Published on 07 September 2026

# 140GH0C4C16

**Allen-Bradley 140G MCCB H Frame 120kA 4P 16A Fixed Thermal Magnetic**


## ENVIRONMENT


| | |
|---|---|
| Rated surrounding temperature without derating | 40 °C |
| Maximum operating temperature | 75 °C |
| Storage temperature | -40…80 °C |
| Max. altitude before derating | 2000 m |

# 140GH0C4C16

**Allen-Bradley 140G MCCB H Frame 120kA 4P 16A Fixed Thermal Magnetic**

## DIMENSIONAL DIAGRAM






Published on 07 September 2026