
140GMTF4D80

Allen-Bradley 140G MCCB M Frame Trip Unit 4P 800A Fixed Thermal Magnetic



Component type	Power switching circuit breaker
Range	Moulded Case Circuit Breaker
Model	N/A
Product status	Existing

The Allen Bradley motor protection circuit breakers offer a reliable solution with both short-circuit and overload protection for individual motor loads with high interrupt ratings for 2 and 3 pole devices. Ideal for motor starting and motor protection applications. Connecting modules are available and have been combination short-circuit tested with the Allen Bradley 100-E contactors.

ELECTRICAL	**Rated current In**	800 A
	Number of poles	4
	Type of protection trip unit	Thermal/magnetic release
	Trip curve	Adj. thermal, adj. magnetic
	Frame size rating	800 A
	Long time overload protection adjustment range	580-800 A
	Instantaneous protection adjustment range	4000-8000 A
	Rated frequency	50-60 Hz
	Rated insulation voltage Ui	1000 V
	Rated impulse withstand voltage Uimp	8 kV
	Complete device with protection unit	No
DIMENSIONS	**Width**	280 mm
ENVIRONMENT	**Rated surrounding temperature without derating**	40 °C
	Maximum operating temperature	75 °C
	Storage temperature	-40…80 °C
	Max. altitude before derating	2000 m

Published on 13 August 2026