

1606XLPRED

Allen-Bradley 1606 Power Supply Compact Redundancy
Module 10 to 60V DC 16A



POWER SUPPLIES



Allen-Bradley



Component type	DC-power supply
Range	1606
Model	N/A
Product status	Existing

The Allen-Bradley 1606 Switched Mode Power Supplies are the ideal solution for reliable and efficient power supply. Features compact design with wide input voltage range (single and multi phase AC and DC), power boosts, in-built redundancy and conformal coating for harsh environments. Available with multiple output voltage levels and wide power output range to accommodate various load sizes.

ELECTRICAL

Voltage type of supply voltage	DC
Frequency	50-60 Hz
Nominal current (In)	8 A
1st secondary output voltage	10-60 V
Max. output current 1	10 A
Nominal value output current 1	16 A
Nominal value output voltage 1	24 V
Power output	384 W
Power consumption	4 VA
Type of electric connection	Spring clamp connection
With LED indication	Yes
Output voltage stabilized	Yes

CONSTRUCTION

Rail mounting possible	Yes
Wall mounting possible	Yes
IP rating	IP20

DIMENSIONS

Width	45 mm
Height	75 mm
Depth	91 mm
Weight	0.14 kg

ENVIRONMENT

Operating temperature	-40...70 °C
Stabilized	Yes