20G11NC5P0AA0NNNNN

Allen-Bradley PowerFlex 755 VSD 400V IP20 5.0A 2.2kW ND/HD Frame 2

LARGE DRIVES



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755
Model	N/A
Alternative	20G11NC5P0JA0NNNNN

Allen-Bradley PowerFlex 755 AC Drives are a simple and high-performance motor control application, providing a variety of solutions including pumps, fans, and conveyors. Featuring a standard built-in Ethernet/IP port, making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware. and safety options.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	400 V
	Nominal output power AC	2.2 kW
	Nominal output current I2N	5 A
	kW rating, normal duty	2.2 kW
	kW rating, heavy duty	2.2 kW
	Dynamic braking transistor	Yes
	Control characteristic	PID
	EMC-version	Yes
COMMUNICATION	Integrated motion function	No
CONSTRUCTION	Suitable for safety functions	Yes
	Contains keypad	No
	Frame size	2
	IP rating	IP20
	Degree of protection (NEMA)	Other
DIMENSIONS	Height	424.2 mm
	Width	135 mm
	Depth	212 mm
	Weight	8 kg
ENVIRONMENT	Operating temperature	-20…60 °C
	Storage temperature	-40…70 °C

Published on 12 August 2026