22003010

Socomec SLBM Load Break Switch Body, Base/DIN Rail mount, 3P 100A

LOAD BREAK SWITCHES



Component type	Switch disconnector
Range	SLBM
Model	N/A
Product status	Existing

The Socomec SLBM Modular Loadbreak Switches are manually operated, modular and multipolar by design. Providing a safe isolation solution for the distribution of electrical power in a range of applications requiring isolation up to 125A. Installation options include DIN rail, panel, or base mounting, they come with direct mount handle or a panel mount handle and shaft.

ELECTRICAL	**Rated operating voltage Ue**	400-690 V
	Max. rated operation voltage Ue AC	800 V
	Rated permanent current at AC-21, 400 V	100 A
	Rated uninterrupted current Iu	100 A
	Number of poles	3
	Rated operation power at AC-23, 400 V	45 kW
	Rated short-time withstand current Icw	2.75 kA
	Type of control element	Other
	Type of electrical connection of main circuit	Screw connection
	Rated operating voltage	400-690 V
	Rated permanent current at AC-23, 400 V	100 A
	Switching power at 400 V	45 kW
	Conditioned rated short-circuit current Iq	25 kA
	Number of auxiliary contacts as normally closed contact	0
	Number of auxiliary contacts as normally open contact	0
	Number of auxiliary contacts as change-over contact	0
	Motor drive optional	No
	Motor drive integrated	No
	Voltage release optional	No
CONSTRUCTION	**Device construction**	Built-in device fixed built-in technique
	Colour control element	Other
	Degree of protection (IP), front side	IP20
	Version as main switch	Yes
	Version as maintenance-/service switch	Yes

Published on 02 November 2026

22003010

Socomec SLBM Load Break Switch Body, Base/DIN Rail mount, 3P 100A

LOAD BREAK SWITCHES

CONSTRUCTION	Version as safety switch	Yes
	Version as emergency stop installation	Yes
	Version as reversing switch	No
	Number of switches	1
	Suitable for front mounting 4-hole	No
	Suitable for front mounting centre	No
	Suitable for distribution board installation	Yes
	Suitable for intermediate mounting	Yes
	Interlockable	Yes
MECHANICAL	Mechanical life (service cycles)	10000 cycles
DIMENSIONS	Height	260 mm
	Width	562 mm
	Depth	289 mm
	Connectable conductor cross section	6-70 mm²

Published on 02 November 2026