

556610

nVent ERIFLEX Earth Braids 75A 10mm² Length 300mm Hole Diameter 6.5mm



FLEXIBLE BUSBARS AND BRAIDS



Component type	Earthing strip preassembled
Range	Earth Braid
Model	N/A
Product status	Existing

The nVent ERIFLEX Earth Braids provide a reliable solution for ensuring safe and efficient electrical grounding in industrial and commercial settings. Made of high-quality materials, such as copper, which provide superior strength, durability, and conductivity, they range from 6-100mm² in size and are available in pre-cut lengths from 100-500mm or in rolls that can be cut to size.



ELECTRICAL	Rated current	75 A
	Conductor material	Copper
	Braided	Yes
	Shape of conductor	Flat
	Conductor surface	Tinned
	Conductor category	Class 5 = flexible
	Cable width approx.	11 mm
	Insulated	No
	With connecting lugs	Yes
	Connection lugs drilled	Yes
CONSTRUCTION	With cable lugs	Yes
	Nominal cross section conductor	10 mm ²
	Hole diameter connection	6.5 mm
	Length	300 mm
	Width	11 mm
	Thickness	1.1 mm
	Weight	0.03 kg
	Cable height approx.	1.1 mm
	Max. operating temperature	105 °C
DIMENSIONS		
ENVIRONMENT		

556610

nVent ERIFLEX Earth Braids 75A 10mm² Length 300mm Hole
Diameter 6.5mm



FLEXIBLE BUSBARS AND BRAIDS



DIMENSIONAL DIAGRAM

