# 100C60UV00

**Allen-Bradley 100C Contactor 30kW 3Pole 32VAC Coil**

CONTACTORS




| | |
|---|---|
| **Component type** | Power contactor, AC switching |
| **Range** | 100C |
| **Model** | N/A |
| **Product status** | Discontinued |

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

| | | |
|---|---|---|
| **ELECTRICAL** | Number of normally open contacts as main contact | 3 |
| | Number of normally closed contacts as main contact | 0 |
| | Rated operation current Ie at AC-3, 400 V | 60 A |
| | Rated operation power at AC-3, 400 V | 32 kW |
| | Rated operation current Ie at AC-1, 400 V | 100 A |
| | Max. rated operation voltage Ue AC | 690 V |
| | Voltage type for actuating | AC |
| | Control supply voltage Us at AC 50HZ | 32 V |
| | Number of auxiliary contacts as normally open contact | 0 |
| | Number of auxiliary contacts as normally closed contact | 0 |
| | Rated operation current Ie at AC-3, 690 V | 34 A |
| | Rated operation power at AC-3, 690 V | 32 kW |
| | Rated operation power at AC-4, 400 V | 13 kW |
| | Control supply voltage Us at AC 60HZ | 36 V |
| | Power consumption, AC coil pickup | 235 VA |
| | Power consumption, AC coil hold-in | 19.6 VA |
| | Type of electrical connection of main circuit | Screw connection |
| | Rated operation current Ie at AC-4, 400 V | 25.5 A |
| **CONSTRUCTION** | IP rating | IP20 |
| | Mounting method | Screw mounting |
| **DIMENSIONS** | Height | 122 mm |
| | Width | 72 mm |
| | Depth | 125.5 mm |
| | Weight | 1.45 kg |



Published on 29 May 2026

## DIMENSIONAL DIAGRAM

