100ES311

Allen-Bradley 100E Auxiliary Contact with 1NO Contact and 1NC Contact

CONTACTORS



Component type	Auxiliary contact block
Range	100E
Model	N/A
Product status	Existing

The Allen-Bradley 100-E next-generation contactors are available in a range of sizes from 9 to 2650 A, reducing width and weight while maximising panel space. The universal electronic AC/DC coil makes selection easy and offers significant energy savings and direct connection to PLCs for contactors above 100 A.

ELECTRICAL	Number of contacts as normally open contact	1
	Number of contacts as normally closed contact	1
	Rated insulation voltage Ui	690 V
	Rated operation current Ie at AC-15, 24 V	6 A
	Rated operation current Ie at AC-15, 120 V	6 A
	Rated operation current Ie at AC-15, 240 V	4 A
	Rated operation current Ie at AC-15, 400 V	3 A
	Rated operation current Ie at DC-13, 24 V	6 A
	Rated operation current Ie at DC-13, 110 V	0.55 A
	Rated operation current Ie at DC-13, 220 V	0.3 A
	Min. contact rating current	50 mA
	Min. contact rating voltage	12 V
	Rated operation current Ie at AC-15, 230 V	4 A
CONSTRUCTION	Mounting method	Side mounting

Published on 14 October 2026