# 100SC37T14BC

**Allen-Bradley 100SC Safety Contactor 18.5kW 3Pole 240VAC Coil 1NO 4NC Contact Auxiliary**

SAFETY CONTACTORS




| | |
|---|---|
| **Component type** | Power contactor, AC switching |
| **Range** | 100SC |
| **Model** | N/A |
| **Product status** | Existing |

The Allen-Bradley Bulletin 100S-C safety contactors provide mechanically linked positively guided or mirror contact performance, required in the feedback circuits of modern safety applications.

| | | |
|---|---|---|
| **ELECTRICAL** | Number of normally open contacts as main contact | 3 |
| | Number of normally closed contacts as main contact | 0 |
| | Rated operation current Ie at AC-3, 400 V | 37 A |
| | Rated operation power at AC-3, 400 V | 20 kW |
| | Rated operation current Ie at AC-1, 400 V | 65 A |
| | Max. rated operation voltage Ue AC | 690 V |
| | Voltage type for actuating | AC |
| | Control supply voltage Us at AC 50HZ | 240 V |
| | Number of auxiliary contacts as normally open contact | 1 |
| | Number of auxiliary contacts as normally closed contact | 4 |
| | Rated operation current Ie at AC-3, 690 V | 21 A |
| | Rated operation power at AC-3, 690 V | 18.5 kW |
| | Rated operation power at AC-4, 400 V | 6.3 kW |
| | Control supply voltage Us at AC 60HZ | 277 V |
| | Power consumption, AC coil pickup | 105 VA |
| | Power consumption, AC coil hold-in | 12.3 VA |
| | Type of electrical connection of main circuit | Screw connection |
| | Rated operation current Ie at AC-4, 400 V | 14 A |
| **CONSTRUCTION** | IP rating | IP20 |
| | Mounting method | DIN-rail/screw |
| **DIMENSIONS** | Height | 81 mm |
| | Width | 54 mm |
| | Depth | 143 mm |
| | Weight | 0.58 kg |





Published on 02 November 2026