1102CBOD93

Allen-Bradley 1102C Vacuum Contactor 3Pole 200A 120V 50Hz and 60Hz Coil

CONTACTORS



Component type	Power contactor, AC switching
Range	Vaccum Contactor
Model	N/A
Product status	Existing

The Allen-Bradley 1102C and 1502 Vacuum Contactors provide motor control systems suitable for harsh, dirty environments. The vacuum technology provides effective arc extinguishing above 600V when using a compact, long-lasting contactor. They are mechanically and electrically interlocked to avoid contactors closing simultaneously.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation current Ie at AC-3, 400 V	200 A
	Rated operation power at AC-3, 400 V	95 kW
	Max. rated operation voltage Ue AC	1500 V
	Voltage type for actuating	AC
	Control supply voltage Us at AC 50HZ	120 V
	Number of auxiliary contacts as normally open contact	1
	Number of auxiliary contacts as normally closed contact	1
	Rated operation power at AC-3, 690 V	185 kW
	Rated operation power at AC-3, 1000 V	280 kW
	Control supply voltage Us at AC 60HZ	120 V
	Power consumption, AC coil pickup	800 VA
	Power consumption, AC coil hold-in	12 VA
	Type of electrical connection of main circuit	Bolt connection
CONSTRUCTION	IP rating	IP00
	Mounting method	Screw mounting
DIMENSIONS	Height	213 mm
	Width	164 mm
	Depth	151 mm
	Weight	5.5 kg

Published on 30 September 2026