

1747AENTR

Allen-Bradley SLC System SLC50X Ethernet Communication
Module 2Copper FE DLR



Component type	PLC communication module
Range	SLC
Model	N/A
Product status	Existing

ELECTRICAL

With optical interface	No
Number of HW-interfaces industrial Ethernet	2
Number of interfaces PROFINET	0
Number of HW-interfaces RS-232	0
Number of HW-interfaces RS-422	0
Number of HW-interfaces RS-485	0
Number of HW-interfaces serial TTY	0
Number of HW-interfaces USB	0
Number of HW-interfaces parallel	0
Number of HW-interfaces Wireless	0
Number of HW-interfaces other	0

COMMUNICATION

Network connection	10/100 Mbit
Supporting protocol for TCP/IP	Yes
Supporting protocol for PROFIBUS	No
Supporting protocol for CAN	No
Supporting protocol for INTERBUS	No
Supporting protocol for ASI	No
Supporting protocol for KNX	No
Supporting protocol for Modbus	No
Supporting protocol for Data-Highway	No
Supporting protocol for DeviceNet	No
Supporting protocol for SUCONET	No
Supporting protocol for LON	No
Supporting protocol for PROFINET IO	No
Supporting protocol for PROFINET CBA	No
Supporting protocol for SERCOS	No

1747AENTR

Allen-Bradley SLC System SLC50X Ethernet Communication
Module 2Copper FE DLR



MID-RANGE CONTROL SYSTEMS



Allen-Bradley

COMMUNICATION

Supporting protocol for Foundation Fieldbus	No
Supporting protocol for EtherNet/IP	Yes
Supporting protocol for AS-Interface Safety at Work	No
Supporting protocol for DeviceNet Safety	No
Supporting protocol for INTERBUS-Safety	No
Supporting protocol for PROFIsafe	No
Supporting protocol for SafetyBUS p	No
Supporting protocol for other bus systems	No

MECHANICAL

Max. shock acceleration	15 g
Max. vibration acceleration	2 m/s ²
Max. vibration frequency, operational	500 Hz

DIMENSIONS

Width	50 mm
Height	118 mm
Depth	87 mm
Weight	0.28 kg

ENVIRONMENT

Rated temperature	0...60 °C
Storage temperature	-40...85 °C
Max. ambient humidity (non-condensing)	95 %