194RNU4001753

Allen-Bradley 194R Disconnect Switch UL Non Fused Base mount 3 Pole 400A



Component type	Switch disconnector
Range	194R Disconnect
Model	N/A
Product status	Existing

The Bulletin 194R range of disconnect switches are rugged, durable and tested to severe utilisation categories AC-22 and AC-23 for use in demanding applications such as food and beverage and material handling. All in a compact footprint to reduce your panel space requirements.

ELECTRICAL	**Rated uninterrupted current Iu**	400 A
	Number of poles	3
	Type of control element	Long turning handle
	Type of electrical connection of main circuit	Screw connection
	Number of auxiliary contacts as normally closed contact	0
	Number of auxiliary contacts as normally open contact	0
	Motor drive integrated	No
	Voltage release optional	No
CONSTRUCTION	**Device construction**	Complete device in housing
	Degree of protection (IP), front side	IP20
	Version as main switch	Yes
	Version as maintenance-/service switch	No
	Version as safety switch	No
	Version as emergency stop installation	No
	Version as reversing switch	No
	Number of switches	1
	Suitable for front mounting 4-hole	No
	Suitable for distribution board installation	Yes
	Interlockable	No
DIMENSIONS	**Height**	406 mm
	Width	230 mm
	Depth	128 mm
	Weight	3 kg
	Connectable conductor cross section	600 mm²

Published on 24 July 2026

194RNU4001753

Allen-Bradley 194R Disconnect Switch UL Non Fused Base mount 3 Pole 400A

ENVIRONMENT	Rated surrounding temperature without derating	60 °C
	Storage temperature	-40…65 °C
	Allowable relative humidity	95 %

Published on 24 July 2026