# 20G11NE2P7AA0NNNNN

**Allen-Bradley PowerFlex 755 VSD 600V IP20 ND 2.7A 2HP or HD 1.7A 1HP Frame 3**

LARGE DRIVES




| | |
|---|---|
| **Component type** | Frequency converter =< 1 kV |
| **Range** | PowerFlex 755 |
| **Model** | N/A |
| **Alternative** | CALL FOR ALTERNATIVE |

Allen-Bradley PowerFlex 755 AC Drives are a simple and high-performance motor control application, providing a variety of solutions including pumps, fans, and conveyors. Featuring a standard built-in Ethernet/IP port, making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware. and safety options.

| | | |
|---|---|---|
| **ELECTRICAL** | Number of phases input | 3 |
| | Nominal input voltage | 600 V |
| | Nominal output power AC | 1.5 kW |
| | Nominal output current I2N | 2.7 A |
| | kW rating, normal duty | 1.5 kW |
| | kW rating, heavy duty | 0.7 kW |
| | Dynamic braking transistor | Yes |
| | Control characteristic | PID |
| | EMC-version | Yes |
| **COMMUNICATION** | Integrated motion function | No |
| **CONSTRUCTION** | Suitable for safety functions | Yes |
| | Contains keypad | No |
| | Frame size | 3 |
| | IP rating | IP20 |
| | Degree of protection (NEMA) | Other |
| **DIMENSIONS** | Height | 454 mm |
| | Width | 190 mm |
| | Depth | 212 mm |
| | Weight | 12 kg |
| **ENVIRONMENT** | Operating temperature | -20…60 °C |
| | Storage temperature | -40…70 °C |



Published on 12 August 2026