20G21GD027JA0NNNNN

Allen-Bradley PowerFlex 755TS VSD 480V IP54 ND 27A 20HP or HD 22A 15HP Frame 3

LARGE DRIVES



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755T
Model	N/A
Product status	Existing

The Allen-Bradley PowerFlex 755T range of variable speed drives are an extension to the PowerFlex 750 drive portfolio providing solutions for harmonic mitigation and regeneration applications. Fitted with TotalFORCE technology they deliver high performance motor control, adaptive control of torque, velocity, position and predictive analytics on the drives health.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	480 V
	Nominal output power AC	15 kW
	Nominal output current I2N	27 A
	kW rating, normal duty	15 kW
	kW rating, heavy duty	11 kW
	Dynamic braking transistor	Yes
	Control characteristic	PID
	EMC-version	Yes
COMMUNICATION	Integrated motion function	No
CONSTRUCTION	Suitable for safety functions	Yes
	Contains keypad	Yes
	Frame size	3
	IP rating	IP20
	Degree of protection (NEMA)	12
DIMENSIONS	Height	551 mm
	Width	268 mm
	Depth	220.1 mm
	Weight	12 kg
ENVIRONMENT	Operating temperature	-20…60 °C
	Storage temperature	-40…70 °C

Published on 06 November 2026

20G21GD027JA0NNNNN

Allen-Bradley PowerFlex 755TS VSD 480V IP54 ND 27A 20HP or HD 22A 15HP Frame 3

LARGE DRIVES

DIMENSIONAL DIAGRAM



Dimensions are in millimeters and (inches).
Weights are in kilograms and (pounds).

Frame	A	B	C	D	E	Weight, kg (lb)
2	215.3 (8.48)	543.2 (21.39)	222.2 (8.75)	100.0 (3.94)	528.2 (20.80)	7.8 (17.2)
3	268.0 (10.55)	551.0 (21.69)	220.1 (8.67)	158.0 (6.22)	533.0 (20.98)	11.8 (26.1)
4	300.0 (11.81)	571.0 (22.48)	220.1 (8.67)	194.0 (7.64)	553.0 (21.77)	13.6 (30.0)
5	348.0 (13.70)	647.0 (25.47)	220.1 (8.67)	238.0 (9.37)	629.0 (24.76)	20.4 (45.0)

Published on 06 November 2026