55400NBB

Austrol Cable Pull Wire Switch Trip Wire Switch 2 Normally Closed Contacts 2 Normally Open Contacts

ELECTRICAL ENGINEERING PRODUCTS



Component type	Emergency stop pull cord switch
Range	NHP Austrol
Model	N/A
Alternative	ZS802O2STWINTP

ELECTRICAL	Number of contacts as normally open contact	2
	Number of contacts as normally closed contact	2
	Rated insulation voltage Ui	600 V
	Rated operation current Ie at AC-15, 240 V	3 A
	Rated operation current Ie at AC-15, 415 V	1.5 A
	Rated operation current Ie at DC-12, 32 V	10 A
	Rated operation current Ie at DC-12, 110 V	5 A
	Rated operation current Ie at DC-12, 240 V	2 A
	Rated operation current Ie at DC-13, 32 V	10 A
	Rated operation current Ie at DC-13, 110 V	2.2 A
	Rated operation current Ie at DC-13, 240 V	1.1 A
CONSTRUCTION	Emergency stop button	No
	Material housing	Aluminium die-cast
	Colour	Yellow
	IP rating	IP65/IP67
DIMENSIONS	Height	189 mm
	Width	284 mm
	Depth	124 mm

Published on 01 June 2026