556630

nVent ERIFLEX Earth Braids 120A 16mm2 Length 150mm Hole Diameter 8.5mm

FLEXIBLE BUSBARS AND BRAIDS

Component type	Earthing strip preassembled
Range	Earth Braid
Model	N/A
Product status	Existing

The nVent ERIFLEX Earth Braids provide a reliable solution for ensuring safe and efficient electrical grounding in industrial and commercial settings. Made of high-quality materials, such as copper, which provide superior strength, durability, and conductivity, they range from 6-100mm2 in size and are available in pre-cut lengths from 100-500mm or in rolls that can be cut to size.

ELECTRICAL	**Rated current**	120 A
CONSTRUCTION	**Conductor material**	Copper
	Braided	Yes
	Shape of conductor	Flat
	Conductor surface	Tinned
	Conductor category	Class 5 = flexible
	Cable width approx.	15 mm
	Insulated	No
	With connecting lugs	Yes
	Connection lugs drilled	Yes
	With cable lugs	Yes
DIMENSIONS	**Nominal cross section conductor**	16 mm²
	Hole diameter connection	8.5 mm
	Length	150 mm
	Width	15 mm
	Thickness	1.5 mm
	Weight	0.02 kg
	Cable height approx.	1.5 mm
ENVIRONMENT	**Max. operating temperature**	105 °C

556630

nVent ERIFLEX Earth Braids 120A 16mm2 Length 150mm Hole Diameter 8.5mm

FLEXIBLE BUSBARS AND BRAIDS

DIMENSIONAL DIAGRAM



Published on 02 October 2026