561134

nVent ERIFLEX High Current Terminal 750A In and Out 1 x M10 Lug 16 to 400mm Busbar 20 to 50mm

TERMINALS AND DISTRIBUTION BLOCKS




Component type	Distributor assembly terminal blocks
Range	High Current Terminal
Model	N/A
Product status	Existing

The nVent ERIFLEX range of high current terminals come in current ratings 80A to 1940A and offer connection ratio with 1 or 2 inputs to 1 or 2 output terminals. Terminals are tin plated to cater for copper or aluminium conductors offering IP2X touch protection.

ELECTRICAL	Number of poles	1
	Rated insulation voltage Ui	1000 V
	Short time withstand current Icw, 1 sec	36 kA
	Max. rated current	750 A
CONSTRUCTION	Conductor material	Aluminium/copper
	With PE-rail	No
	With N-rail	No
DIMENSIONS	Conductor cross section flexible (fine-strand) with cable end sleeve	16-400 mm²
	Conductor cross section (solid, stranded)	400-16 mm²
	Height	205.7 mm
	Width	85.1 mm
	Depth	65 mm

Published on 02 October 2026

DIMENSIONAL DIAGRAM



RELATED PRODUCTS

ACCESSORY



Item No: 561138
Required: No
Description: nVent ERIFLEX High Current Terminal End Clamp for DIN35 Mount or Panel Mount