700HA33Z24

Allen-Bradley 700-HA General Purpose Tube Base Relay 10A 3 Changeover 3PDT 24V DC Coil

GENERAL PURPOSE RELAYS

Allen-Bradley

Component type	Switching relay
Range	Panel Mount and Power Relays
Model	N/A
Product status	Existing

ELECTRICAL	Nominal current	10 A
	Nominal voltage AC	250 V
	Number of contacts as change-over contact	3
	Rated switching power at AC-1	2500 VA
	Rated switching power at AC-15, 230V	500 VA
	Breaking capacity at DC-1, 30V	10 A
	Voltage type for actuating	DC
	Control supply voltage Us at DC	24 V
	Type of electric connection	Plug-in connection
	Electrical life at Un, In (service cycles)	100000 cycles
CONSTRUCTION	Material contact	Silver nickel
	Suitable for plug-in socket mounting	Yes
	IP rating	IP40
MECHANICAL	Mechanical life (service cycles)	5.0E7 cycles
	Max. shock acceleration	50 g
	Max. vibration acceleration	5 m/s²
DIMENSIONS	Width	32.8 mm
	Height	36.5 mm
	Depth	54.1 mm
ENVIRONMENT	Operating temperature	-40…70 °C

Published on 30 September 2026

700HA33Z24

Allen-Bradley 700-HA General Purpose Tube Base Relay 10A 3 Changeover 3PDT 24V DC Coil

GENERAL PURPOSE RELAYS

DIMENSIONAL DIAGRAM





Published on 30 September 2026