CA8P13

S+S CA8 Auxiliary Contact with 1NO Contact and 3NC Contact

CONTACTORS



Component type	Auxiliary contact block
Range	CA8 Mini
Model	N/A
Product status	Existing

The Sprecher + Schuh CA8 miniature contactors and starters are a compact and reliable method of controlling motors of 5.5kW or less. Ideal for applications where space is limited. Components are DIN-rail mountable and clearly marked and dispatched in the open position ready for assembly. Fittings are also included on the base mounting for quick installation and modification.

ELECTRICAL	**Number of contacts as normally open contact**	1
	Number of contacts as normally closed contact	3
	Rated insulation voltage Ui	690 V
	Rated operation current Ie at AC-15, 24 V	3 A
	Rated operation current Ie at AC-15, 120 V	3 A
	Rated operation current Ie at AC-15, 240 V	2 A
	Rated operation current Ie at AC-15, 400 V	1.2 A
	Rated operation current Ie at DC-13, 24 V	2.3 A
	Rated operation current Ie at DC-13, 110 V	0.55 A
	Rated operation current Ie at DC-13, 220 V	0.27 A
	Min. contact rating current	2 mA
	Min. contact rating voltage	15 V
	Rated operation current Ie at AC-15, 230 V	2 A
CONSTRUCTION	**Mounting method**	Top mounting

Published on 30 May 2026