CSB36ST

NHP MOD6 CSB Insulated Loadcentre 36 Way DIN Surface Door Transparent

MOD6
LOADCENTRES AND POLE COVERS



Component type	Small distribution board
Range	CSB
Model	N/A
Product status	Discontinued

NHP's CSB surface-mounted insulated loadcentres offer a compact, cost effective method of mounting DIN circuit protective devices in domestic or commercial settings. The CSB loadcentres can accommodate a wide range of current ratings, making them suitable for various applications. The CSB surface or flush-mount options range from 8 up to 36 way with either transparent or white door.

ELECTRICAL	**Rated current In**	100 A
	Number of outgoing ways	36
	Number of poles, 18mm pitch	36
	Max. rated operation voltage Ue AC	415 V
	Rated insulation voltage Ui	500 V
	Neutral terminal block	Yes
	Neutral bar rated current	100 A
	Earthing terminal block	Yes
CONSTRUCTION	**Spare DIN equipment space (poles)**	36
	DIN-rail	Yes
	Number of rows	3
	Material housing	Plastic
	Colour	White
	IP rating	IP40
	Type of cover	Door
	Transparent cover/door	Yes
	With lock	No
	Mounting method	Surface mounted (plaster)
DIMENSIONS	**Width in number of modular spacings**	12
	Height	473 mm
	Width	306 mm
	Depth	102 mm

Published on 02 September 2026

CSB36ST

NHP MOD6 CSB Insulated Loadcentre 36 Way DIN Surface Door Transparent

MOD6
LOADCENTRES AND POLE COVERS

RELATED PRODUCTS

ACCESSORY

Item No: CSB36FMPL

Required: No

Description: NHP MOD6 CSB Insulated Loadcentre Metal Back Mounting Plate Long suits CSB36 Flush

Published on 02 September 2026